

## LIGHT STRIPE 1500 MM DIMMABLE I-10V

<b>Number of heads</b>	1
<b>Mounting</b>	Track mounting
<b>Lamps description</b>	Top LED 30W 2788 lm 2700K CRI 90
<b>Luminaire luminous flux</b>	See reference number
<b>Voltage (V)</b>	48
<b>Environment</b>	Indoor
<b>Notes</b>	Only compatible with DALI, I-10V, FLOS SMART CONTROL profile version.



### OPTICAL

<b>Aiming</b>	Fixed
<b>Light distribution symmetry</b>	Symmetric
<b>Beam angle</b>	111°


**Light Stripe 1500 mm Dimmable I-10V**  
designed by FLOS Architectural

Diffused LED light module to be installed in The Tracking Magnet System.

### ELECTRICAL

<b>Transformer availability</b>	Separate item
<b>Transformer mounting</b>	Remote
<b>Transformer type</b>	Electronic dimmable I-10V
<b>Emergency</b>	Without

● 03.8004.14.1V - 1220lm Black



### CERTIFICATIONS



## Light Stripe 1500 mm Dimmable 1-10V . Lamps



**Top LED**

**Lamp category:**

LED

**Socket:**

Special base

**Lamp type:**


Top LED



**Light Stripe 1500 mm Dimmable 1-10V**  
designed by FLOS Architectural

Diffused LED light module to be installed in The Tracking Magnet System.

● 03.8004.14.1V - 1220lm Black



**CERTIFICATIONS**

