

SPOT 150 ON BOARD DIMMER

Number of heads

Mounting Track mounting

LED Array 22,5W 2115 lm 3000K CRI 90 Lamps description

Luminaire luminous flux See reference number

Voltage (V) 48 **Environment** Indoor

Notes Screening crosspiece, lenses and honeycomb directly

installable on the head of the luminaire without needing any fastening accessory. Installation compatible with

honeycomb + lense at the same time.

OPTICAL

Aiming Adjustable Light distribution symmetry Symmetric Beam angle 16° Spot

ELECTRICAL

Transformer availability Separate item Transformer mounting Remote

Transformer type Electronic dimmable

Emergency Without Class III **Insulation class**

PHYSICAL

Spot diameter (mm) 57

Construction material Aluminium Weight (kg) 0,30






Spot 150 On Board Dimmer designed by FLOS Architectural

<div>Accent lighting LED module to
be installed in The Tracking Magnet/ Infra-Structure System.</div>

03.8073.40 - 1872lm White 03.8073.05 - 1872lm Chrome 03.8073.14 - 1872lm Black



CERTIFICATIONS

















ΙP 20

Flos.architectural@flos.com www.flos.com



Spot 150 On Board Dimmer . Accessories

Optical







08.8429.00

Screening Crosspiece

08.8431.00 Elliptical Lens

08.8432.00


Flood Lens



Spot 150 On Board Dimmer designed by FLOS Architectural

<div>Accent lighting LED module to be installed in The Tracking Magnet/ Infra-Structure System.</div>

03.8073.40 - 1872lm White
03.8073.05 - 1872lm Chrome
03.8073.14 - 1872lm Black





08.8428.00

Honeycomb



08.0526.00

Snoot Shielding Cone

CERTIFICATIONS

















IP 20

Flos.architectural@flos.com www.flos.com



Spot 150 On Board Dimmer . Lamps



LED Array

Lamp category:

LED

Socket:

Special base

Lamp type:


LED Array



Spot 150 On Board Dimmer designed by FLOS Architectural

<div>Accent lighting LED module to be installed in The Tracking Magnet/ Infra-Structure System.</div>

03.8073.40 - 1872lm White
03.8073.05 - 1872lm Chrome
03.8073.14 - 1872lm Black



CERTIFICATIONS











IP 20







Flos.architectural@flos.com www.flos.com