

# FLOS

## SPOT 150 DALI VERSION

<b>Number of heads</b>	1
<b>Mounting</b>	Track mounting
<b>Lamps description</b>	LED Array 22,5W 2000 lm 2700K CRI 90
<b>Luminaire luminous flux</b>	See reference number
<b>Voltage (V)</b>	48
<b>Environment</b>	Indoor
<b>Notes</b>	Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time. Only compatible with DALI, I-10V, FLOS SMART CONTROL profile version.



**Spot 150 Dali Version**  
designed by FLOS Architectural

<div>Accent lighting LED module to be installed in The Tracking Magnet/ Infra-Structure System.</div>

### OPTICAL

<b>Aiming</b>	Adjustable
<b>Light distribution symmetry</b>	Symmetric
<b>Beam angle</b>	28° Medium


### ELECTRICAL

<b>Transformer availability</b>	Separate item
<b>Transformer mounting</b>	Remote
<b>Transformer type</b>	Electronic dimmable dali
<b>Emergency</b>	Without
<b>Insulation class</b>	Class III



- 03.8074.40.DA - 1717lm White
- 03.8074.05.DA - 1717lm Chrome
- 03.8074.14.DA - 1717lm Black

### PHYSICAL

<b>Spot diameter (mm)</b>	57
<b>Construction material</b>	Aluminium
<b>Weight (kg)</b>	0,30



### CERTIFICATIONS



## Spot 150 Dali Version . Accessories

### Optical



● 08.8429.00

**Screening Crosspiece**



○ 08.8431.00

**Elliptical Lens**



○ 08.8432.00

**Flood Lens**



● 08.8428.00

**Honeycomb**



● 08.0526.00


**Snoot Shielding Cone**





**Spot 150 Dali Version**  
designed by FLOS Architectural

<div>Accent lighting LED module to be installed in The Tracking Magnet/ Infra-Structure System.</div>

- 03.8074.40.DA - 1717lm White
- 03.8074.05.DA - 1717lm Chrome
- 03.8074.14.DA - 1717lm Black



### CERTIFICATIONS



## Spot 150 Dali Version . Lamps



**LED Array**

**Lamp category:**

LED

**Socket:**

Special base

**Lamp type:**

LED Array




**Spot 150 Dali Version**

designed by FLOS Architectural

<div>Accent lighting LED module to be installed in The Tracking Magnet/ Infra-Structure System.</div>

- 03.8074.40.DA - 1717lm White
- 03.8074.05.DA - 1717lm Chrome
- 03.8074.14.DA - 1717lm Black



**CERTIFICATIONS**

