FLOS

SUSPENSION GLASS DOWNLIGHT 110 BLACK ROD 400 MM ON BOARD DIMMER

L

Fixed

L

Symmetric

- Number of heads Mounting Lamps description Luminaire luminous flux Voltage (V) Environment
- Track mounting LED Array 13,5W 1296 Im 2700K CRI 90 Extreme Cut-off. See reference number 48 Indoor

OPTICAL

Aiming Light distribution symmetry

ELECTRICAL

- Transformer availability Transformer mounting Transformer type Emergency Insulation class
- Separate item Remote Electronic dimmable Without Class III

PHYSICAL

Weight (kg)






Suspension Glass Downlight 110 Black Rod 400 mm On Board Dimmer


designed by Vincent Van Duysen

<div>Suspended luminaire with rigid rod and blown glass in several finishes to be installed in the Infra-Structure system.</div>

03.8131.00 - 82° - 706lm Transparent Glass 03.8131.FU - 47° - 483lm Smoked Glass 03.8131.RC - 42° - 292lm Red Glass



CERTIFICATIONS



FLOS

Suspension Glass Downlight 110 Black Rod 400 mm On Board Dimmer . Lamps



LED Array LED Socket: Special base Lamp type: LED Array




Suspension Glass Downlight 110 Black Rod 400 mm On Board Dimmer

designed by Vincent Van Duysen

<div>Suspended luminaire with rigid rod and blown glass in several finishes to be installed in the Infra-Structure system.</div>

03.8131.00 - 82° - 706lm Transparent Glass
03.8131.FU - 47° - 483lm Smoked Glass
03.8131.RC - 42° - 292lm Red Glass



CERTIFICATIONS

