

SUSPENSION GLASS DOWNLIGHT I 10 BLACK ROD 400 MM DIMMABLE I-10V

Number of heads	I
Mounting	Track mounting
Lamps description	LED Array 13,5W 1371 lm 3000K CRI 90
Luminaire luminous flux	Extreme Cut-off. See reference number
Voltage (V)	48
Environment	Indoor
Notes	Only compatible with DALI, I-10V, FLOS SMART CONTROL profile version.

OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric

ELECTRICAL

Transformer availability	Separate item
Transformer mounting	Remote
Transformer type	Electronic dimmable I-10V
Emergency	Without
Insulation class	Class III

PHYSICAL

Weight (kg)	I
--------------------	---




Suspension Glass Downlight I 10 Black Rod 400 mm Dimmable I-10V



designed by Vincent Van Duysen

<div>Suspended luminaire with rigid rod and blown glass in several finishes to be installed in the Infra-Structure system.</div>

- 03.8133.00.IV - 82° - 746lm Transparent Glass
- 03.8133.FU.IV - 47° - 510lm Smoked Glass
- 03.8133.RC.IV - 42° - 309lm Red Glass



CERTIFICATIONS



Suspension Glass Downlight I 10 Black Rod 400 mm Dimmable I-10V . Lamps



LED Array

Lamp category:

LED

Socket:

Special base

Lamp type:

LED Array




Suspension Glass Downlight I 10 Black Rod 400 mm Dimmable I-10V

designed by Vincent Van Duysen

Suspended luminaire with rigid rod and blown glass in several finishes to be installed in the Infra-Structure system.

- 03.8133.00.IV - 82° - 746lm Transparent Glass
- 03.8133.FU.IV - 47° - 510lm Smoked Glass
- 03.8133.RC.IV - 42° - 309lm Red Glass



CERTIFICATIONS

