FLOS

LIGHT SHADOW FIXED NO TRIM 2 SPOTS OPTIC SPOT

Mounting Lamps description Luminaire luminous flux Environment Notes Ceiling recessed Power LED 5,4W 560 Im 3000K CRI 90 Extreme Cut-off. See reference number Indoor It requires an pre-installation frame, to be ordered separately.

OPTICAL

AimingFixedLight distribution symmetrySymmetricBeam angle10° Spot

ELECTRICAL

Transformer availability	Included
Transformer mounting	Remote
Transformer type	Electronic
Emergency	Without
Insulation class	Class II

PHYSICAL

Length (mm)	70
Recessed depth (mm)	75
Weight (kg)	0,25






Light Shadow Fixed No Trim 2 Spots Optic Spot


designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

🕖 03.8856.40 - 432lm	White / White
03.8856.14 - 432lm	Black / White
🖉 03.8858.40 - 435lm	White / Chrome
🚺 03.8858.14 - 435lm	Black / Chrome
🥖 03.8859.40 - 429lm	White / Matt Gold
🏉 03.8859.14 - 429lm	Black / Matt Gold
03.8857.40 - 423lm	White / Black
03.8857.14 - 423lm	Black / Black



CERTIFICATIONS



FLOS

Light Shadow Fixed No Trim 2 Spots Optic Spot . Accessories

Mounting





08.0510.00

Pre-installation frame. Fixed No Trim 2L

08.0052.90

Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim preinstallation frames.

Light Shadow Fixed No Trim 2 Spots Optic Spot . Lamps



Power LED LED Socket: Special base Lamp type: Power LED



Light Shadow Fixed No Trim 2 Spots Optic Spot designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

03.8856.40 - 432lm	White / White
03.8856.14 - 432lm	Black / White
🥒 03.8858.40 - 435lm	White / Chrome
🚺 03.8858.14 - 435lm	Black / Chrome
🥖 03.8859.40 - 429lm	White / Matt Gold
🏉 03.8859.14 - 429lm	Black / Matt Gold
0 3.8857.40 - 423lm	White / Black
03.8857.14 - 423lm	Black / Black

