

#### **LIGHT SHADOW FIXED NO TRIM 8 SPOTS OPTIC SPOT**

**Mounting** Ceiling recessed

Lamps descriptionPower LED 21,6W 2080 Im 2700K CRI 90Luminaire luminous fluxExtreme Cut-off. See reference number

**Environment** Indoor

Notes It requires an pre-installation frame, to be ordered separately.

### **OPTICAL**

Aiming Fixed
Light distribution symmetry Symmetric
Beam angle 10° Spot

#### **ELECTRICAL**

Transformer availability Included
Transformer mounting Remote
Transformer type Electronic
Emergency Without
Insulation class Class II

#### **PHYSICAL**

 Length (mm)
 280

 Recessed depth (mm)
 75

 Weight (kg)
 0,50






#### Light Shadow Fixed No Trim 8 Spots Optic Spot

designed by FLOS Architectural

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included.





# **CERTIFICATIONS**


















# Light Shadow Fixed No Trim 8 Spots Optic Spot . Accessories

## Mounting





08.0512.00

08.0052.90

Pre-installation frame. Fixed No Trim 8L

Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim preinstallation frames.

# **Light Shadow Fixed No Trim 8 Spots Optic Spot . Lamps**



**Power LED** 

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED




Light Shadow Fixed No Trim 8 Spots Optic Spot

designed by FLOS Architectural

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included.

03.8868.40 - 1620lm	White / White
<b>0</b> 3.8868.14 - 1620lm	Black / White
03.8870.40 - 1631lm	White / Chrome
03.8870.14 - 1631lm	Black / Chrome
→ 03.8871.40 - 1607lm	White / Matt Gold
<b>0</b> 3.8871.14 - 1607lm	Black / Matt Gold
<b>3.8869.40 - 1586lm</b>	White / Black
03.8869.14 - 1586lm	Black / Black



# CERTIFICATIONS













