# FLOS

## LIGHT SHADOW FIXED NO TRIM 8 SPOTS OPTIC SPOT

Mounting Lamps description Luminaire luminous flux Environment Notes Ceiling recessed Power LED 21,6W 2240 Im 3000K CRI 90 Extreme Cut-off. See reference number Indoor It requires an pre-installation frame, to be ordered separately.

# OPTICAL

AimingFixedLight distribution symmetrySymmetricBeam angle10° Spot

### ELECTRICAL

Transformer availability	Included
Transformer mounting	Remote
Transformer type	Electronic
Emergency	Without
Insulation class	Class II

## PHYSICAL

Length (mm)	280
Recessed depth (mm)	75
Weight (kg)	0,50







#### Light Shadow Fixed No Trim 8 Spots Optic Spot


designed by FLOS Architectural

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included.

03.8872.40 - 1729lm	White / White
Ø3.8872.14 - 1729lm	Black / White
alian 03.8874.40 - 17411m	White / Chrome
🜑 03.8874.14 - 17411m	Black / Chrome
🥖 03.8875.40 - 1715lm	White / Matt Gold
🏉 03.8875.14 - 1715lm	Black / Matt Gold
🥒 03.8873.40 - 1692lm	White / Black
03.8873.14 - 1692lm	Black / Black







# FLOS

# Light Shadow Fixed No Trim 8 Spots Optic Spot . Accessories

#### Mounting





08.0512.00

08.0052.90

Pre-installation frame. Fixed No Trim 8L

Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim preinstallation frames.

## Light Shadow Fixed No Trim 8 Spots Optic Spot . Lamps



Power LED LED Socket: Special base Lamp type: Power LED



Light Shadow Fixed No Trim 8 Spots Optic Spot designed by FLOS Architectural

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included.

03.8872.40 - 1729lm	White / White
03.8872.14 - 1729lm	Black / White
03.8874.40 - 17411m	White / Chrome
03.8874.14 - 17411m	Black / Chrome
03.8875.40 - 1715lm	White / Matt Gold
03.8875.14 - 1715lm	Black / Matt Gold
03.8873.40 - 1692lm	White / Black
03.8873.14 - 1692lm	Black / Black

