FLOS

LIGHT SHADOW ADJUSTABLE NO TRIM 2 SPOTS OPTIC SPOT

Adjustable

10° Spot

Mounting Lamps description Luminaire luminous flux Environment Notes

Ceiling recessed Power LED 5,4W 520 Im 2700K CRI 90 Extreme Cut-off. See reference number Indoor It requires an pre-installation frame, to be ordered separately.

OPTICAL

Aiming Light distribution symmetry Symmetric **B**eam angle

ELECTRICAL

Included
Remote
Electronic
Without
Class II

PHYSICAL

Recessed depth (mm)	75
Weight (kg)	0,25




Light Shadow Adjustable No Trim 2 Spots Optic Spot


designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

🕖 03.8916.40 - 405lm	White / White
Ø3.8916.14 - 405lm	Black / White
alian	White / Chrome
🚺 03.8918.14 - 408lm	Black / Chrome
🥖 03.8919.40 - 402lm	White / Matt Gold
🏉 03.8919.14 - 402lm	Black / Matt Gold
🕑 03.8917.40 - 396lm	White / Black
03.8917.14 - 396lm	Black / Black



CERTIFICATIONS CE GWT F **K**03 850° PENDING IP $\mathbf{\mathbf{U}}$ 44 30° 30°



FLOS

Light Shadow Adjustable No Trim 2 Spots Optic Spot . Accessories

Mounting





08.0515.00

Pre-installation frame. Adjustable No Trim 2L

08.0059.90

Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim preinstallation frames.

Light Shadow Adjustable No Trim 2 Spots Optic Spot . Lamps



Power LED LED Socket: Special base Lamp type: Power LED



Light Shadow Adjustable No Trim 2 Spots Optic Spot designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

0 ()	3.8916.40 - 405lm	White / White
(0	3.8916.14 - 405lm	Black / White
0	3.8918.40 - 408lm	White / Chrome
0 🥒	3.8918.14 - 408lm	Black / Chrome
0 🥥	3.8919.40 - 402lm	White / Matt Gold
/ 0	3.8919.14 - 402lm	Black / Matt Gold
0	3.8917.40 - 396lm	White / Black
0	3.8917.14 - 396lm	Black / Black

