# FLOS

# LIGHT SHADOW ADJUSTABLE NO TRIM 2 SPOTS OPTIC SPOT

Adjustable

10° Spot

Mounting Lamps description Luminaire luminous flux Environment Notes

Ceiling recessed Power LED 5,4W 560 Im 3000K CRI 90 Extreme Cut-off. See reference number Indoor It requires an pre-installation frame, to be ordered separately.

# OPTICAL

Aiming Light distribution symmetry Symmetric **B**eam angle

### ELECTRICAL

Included
Remote
Electronic
Without
Class II

# PHYSICAL

Recessed depth (mm)	75
Weight (kg)	0,25





# Light Shadow Adjustable No Trim 2 Spots Optic Spot


designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

🖉 03.8920.40 - 432lm	White / White
♥ 03.8920.14 - 432lm	Black / White
alion 03.8922.40 - 435lm	White / Chrome
🖉 03.8922.14 - 435lm	Black / Chrome
🥖 03.8923.40 - 429lm	White / Matt Gold
🏉 03.8923.14 - 429lm	Black / Matt Gold
🕑 03.8921.40 - 423lm	White / Black
03.8921.14 - 423lm	Black / Black







# FLOS

# Light Shadow Adjustable No Trim 2 Spots Optic Spot . Accessories

#### Mounting





08.0515.00

Pre-installation frame. Adjustable No Trim 2L

08.0059.90

# Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim preinstallation frames.

Light Shadow Adjustable No Trim 2 Spots Optic Spot . Lamps



Power LED LED Socket: Special base Lamp type: Power LED



### Light Shadow Adjustable No Trim 2 Spots Optic Spot designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

0	3.8920.40 - 432lm	White / White
<b>(</b> 0	3.8920.14 - 432lm	Black / White
0	3.8922.40 - 435lm	White / Chrome
0	3.8922.14 - 435lm	Black / Chrome
0 🥖	3.8923.40 - 429lm	White / Matt Gold
0	3.8923.14 - 429lm	Black / Matt Gold
0	3.8921.40 - 423lm	White / Black
0	3.8921.14 - 423lm	Black / Black

