FLOS

LIGHT SHADOW ADJUSTABLE NO TRIM 8 SPOTS OPTIC SPOT

Mounting Lamps description Luminaire luminous flux Environment Notes Ceiling recessed Power LED 21,6W 2080 Im 2700K CRI 90 Extreme Cut-off. See reference number Indoor It requires an pre-installation frame, to be ordered separately.

OPTICAL

AimingAdjustableLight distribution symmetrySymmetricBeam angle10° Spot

ELECTRICAL

Transformer availability	Included
Transformer mounting	Remote
Transformer type	Electronic
Emergency	Without
Insulation class	Class II

PHYSICAL

Recessed depth (mm)	75
Weight (kg)	0,50




Light Shadow Adjustable No


Light Shadow Adjustable No Trim 8 Spots Optic Spot


designed by FLOS Architectural

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included.

🕖 03.8932.40 - 1620lm	White / White
Ø3.8932.14 - 1620lm	Black / White
🥒 03.8934.40 - 16311m	White / Chrome
🖉 03.8934.14 - 16311m	Black / Chrome
🥖 03.8935.40 - 1607lm	White / Matt Gold
🏉 03.8935.14 - 1607lm	Black / Matt Gold
🖌 03.8933.40 - 1586lm	White / Black
03.8933.14 - 1586lm	Black / Black







FLOS

Light Shadow Adjustable No Trim 8 Spots Optic Spot . Accessories

Mounting





08.0517.00

Pre-installation frame. Adjustable No Trim 8L

08.0059.90

Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim preinstallation frames.

Light Shadow Adjustable No Trim 8 Spots Optic Spot . Lamps



Power LED LED Socket: Special base Lamp type: Power LED



Light Shadow Adjustable No Trim 8 Spots Optic Spot designed by FLOS Architectural

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included.

🕖 03.8932.40 - 1620lm	White / White
Ø3.8932.14 - 1620lm	Black / White
🥒 03.8934.40 - 16311m	White / Chrome
🔵 03.8934.14 - 16311m	Black / Chrome
🥖 03.8935.40 - 1607lm	White / Matt Gold
🏉 03.8935.14 - 1607lm	Black / Matt Gold
🕖 03.8933.40 - 1586lm	White / Black
🖉 03.8933.14 - 1586lm	Black / Black

