# FLOS

# LIGHT SHADOW ADJUSTABLE NO TRIM 12 SPOTS OPTIC SPOT

Included

Remote

Electronic

Without

Class II

75 0,66

Mounting Lamps description Luminaire luminous flux Environment Notes Ceiling recessed Power LED 32,4W 3120 Im 2700K CRI 90 Extreme Cut-off. See reference number Indoor It requires an pre-installation frame, to be ordered separately.

# OPTICAL

AimingAdjustableLight distribution symmetrySymmetricBeam angle10° Spot

## ELECTRICAL

Transformer availability Transformer mounting Transformer type Emergency Insulation class

# PHYSICAL


Recessed depth (mm)	
Weight (kg)	


# Light Shadow Adjustable No Trim 12 Spots Optic Spot


designed by FLOS Architectural

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included.

🖉 03.8940.40 - 2430lm	White / White
03.8940.14 - 2430lm	Black / White
at 2447lm 03.8942.40 - 2447lm	White / Chrome
🖉 03.8942.14 - 2447lm	Black / Chrome
🥖 03.8943.40 - 241 Ilm	White / Matt Gold
💋 03.8943.14 - 24111m	Black / Matt Gold
🟉 03.8941.40 - 2379lm	White / Black
03.8941.14 - 2379lm	Black / Black







# FLOS

# Light Shadow Adjustable No Trim 12 Spots Optic Spot . Accessories

## Mounting



Light Shadow Adjustable No Trim 12 Spots Optic Spot . Lamps



Power LED LED Socket: Special base Lamp type: Power LED



designed by FLOS Architectural

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included.

03.8940.40 - 2430lm	White / White
Ø3.8940.14 - 2430lm	Black / White
🥒 03.8942.40 - 2447lm	White / Chrome
🚺 03.8942.14 - 2447lm	Black / Chrome
🥖 03.8943.40 - 241 I lm	White / Matt Gold
🏉 03.8943.14 - 24111m	Black / Matt Gold
🟉 03.8941.40 - 2379lm	White / Black
03.8941.14 - 2379lm	Black / Black

