## FLOS

### LIGHT SHADOW FIXED NO TRIM 2 SPOTS OPTIC MEDIUM

Fixed

Symmetric

23° Medium

Mounting Lamps description Luminaire luminous flux Environment Notes Ceiling recessed Power LED 5,4W 520 Im 2700K CRI 90 Extreme Cut-off. See reference number Indoor It requires an pre-installation frame, to be ordered separately.

### OPTICAL

Aiming Light distribution symmetry Beam angle

### ELECTRICAL

Transformer availability	Included
Transformer mounting	Remote
Transformer type	Electronic
Emergency	Without
Insulation class	Class II

### PHYSICAL

Length (mm)	70
Recessed depth (mm)	75
Weight (kg)	0,25






#### Light Shadow Fixed No Trim 2 Spots Optic Medium


designed by FLOS Architectural

<div>Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.</div>

🕖 03.9200.40 - 395lm	White / White
Ø3.9200.14 - 395lm	Black / White
🥒 03.9202.40 - 400lm	White / Chrome
🖉 03.9202.14 - 400lm	Black / Chrome
🥖 03.9203.40 - 393lm	White / Matt Gold
🏉 03.9203.14 - 393lm	Black / Matt Gold
🖌 03.9201.40 - 388lm	White / Black
🕖 03.9201.14 - 388lm	Black / Black



### CERTIFICATIONS E GWT B500 B HP 44



## FLOS

### Light Shadow Fixed No Trim 2 Spots Optic Medium . Accessories

#### Mounting





08.0510.00

Pre-installation frame. Fixed No Trim 2L

08.0052.90

### Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim preinstallation frames.

### Light Shadow Fixed No Trim 2 Spots Optic Medium . Lamps



Power LED LED Socket: Special base Lamp type: Power LED




### Light Shadow Fixed No Trim 2 Spots Optic Medium

designed by FLOS Architectural

<div>Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.</div>

🖉 03.9200.40 - 395lm	White / White
Ø3.9200.14 - 395lm	Black / White
🥒 03.9202.40 - 400lm	White / Chrome
🖉 03.9202.14 - 400lm	Black / Chrome
🥖 03.9203.40 - 393lm	White / Matt Gold
🏉 03.9203.14 - 393lm	Black / Matt Gold
🥒 03.9201.40 - 388lm	White / Black
🕖 03.9201.14 - 388lm	Black / Black



# CERTIFICATIONS

