FLOS

LIGHT SHADOW FIXED NO TRIM 2 SPOTS OPTIC FLOOD

Mounting Lamps description Luminaire luminous flux Environment Notes Ceiling recessed Power LED 5,4W 520 Im 2700K CRI 90 Extreme Cut-off. See reference number Indoor It requires an pre-installation frame, to be ordered separately.

OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	33° Flood

ELECTRICAL

Transformer availability	Included
Transformer mounting	Remote
Transformer type	Electronic
Emergency	Without
Insulation class	Class II

PHYSICAL

Length (mm)	70
Recessed depth (mm)	75
Weight (kg)	0,25






Light Shadow Fixed No Trim 2 Spots Optic Flood


designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

🖉 03.9205.40 - 394lm	White / White
Ø3.9205.14 - 394lm	Black / White
alim 03.9207.40 - 403lm	White / Chrome
🔵 03.9207.14 - 403lm	Black / Chrome
🥖 03.9208.40 - 390lm	White / Matt Gold
🏉 03.9208.14 - 390lm	Black / Matt Gold
🟉 03.9206.40 - 383lm	White / Black
03.9206.14 - 383lm	Black / Black



CERTIFICATIONS



FLOS

Light Shadow Fixed No Trim 2 Spots Optic Flood . Accessories

Mounting





08.0510.00

Pre-installation frame. Fixed No Trim 2L

08.0052.90

Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim preinstallation frames.

Light Shadow Fixed No Trim 2 Spots Optic Flood . Lamps



Power LED LED Socket: Special base Lamp type: Power LED



Light Shadow Fixed No Trim 2 Spots Optic Flood

designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

🖉 03.9205.40 - 394lr	n White / White
Ø3.9205.14 - 394lr	n Black / White
🥥 03.9207.40 - 403lr	m White / Chrome
🔵 03.9207.14 - 403lr	m Black / Chrome
🥖 03.9208.40 - 390lr	m White / Matt Gold
🏉 03.9208.14 - 390lr	m Black / Matt Gold
🥒 03.9206.40 - 383lr	m White / Black
03.9206.14 - 383lr	n Black / Black

