# FLOS

### LIGHT SHADOW FIXED NO TRIM 2 SPOTS OPTIC MEDIUM

Fixed

Symmetric

23° Medium

Mounting Lamps description Luminaire luminous flux Environment Notes Ceiling recessed Power LED 5,4W 560 Im 3000K CRI 90 Extreme Cut-off. See reference number Indoor It requires an pre-installation frame, to be ordered separately.

### OPTICAL

Aiming Light distribution symmetry Beam angle

### ELECTRICAL

Included
Remote
Electronic
Without
Class II

### PHYSICAL

Length (mm)	70
Recessed depth (mm)	75
Weight (kg)	0,25







#### Light Shadow Fixed No Trim 2 Spots Optic Medium


designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

🕖 03.9210.40 - 4211m	White / White
Ø3.9210.14 - 4211m	Black / White
🖉 03.9212.40 - 427lm	White / Chrome
🚺 03.9212.14 - 427lm	Black / Chrome
🥖 03.9213.40 - 419lm	White / Matt Gold
🏉 03.9213.14 - 419lm	Black / Matt Gold
🟉 03.9211.40 - 414lm	White / Black
03.9211.14 - 414lm	Black / Black







# FLOS

### Light Shadow Fixed No Trim 2 Spots Optic Medium . Accessories

#### Mounting





08.0510.00

Pre-installation frame. Fixed No Trim 2L

08.0052.90

# Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim preinstallation frames.

### Light Shadow Fixed No Trim 2 Spots Optic Medium . Lamps



Power LED LED Socket: Special base Lamp type: Power LED



## Light Shadow Fixed No Trim 2 Spots Optic Medium

designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

03.9210.40 - 4211m	White / White
03.9210.14 - 4211m	Black / White
🥒 03.9212.40 - 427lm	White / Chrome
🖉 03.9212.14 - 427lm	Black / Chrome
🥖 03.9213.40 - 419lm	White / Matt Gold
🏉 03.9213.14 - 419lm	Black / Matt Gold
🟉 03.9211.40 - 414lm	White / Black
🕖 03.9211.14 - 414lm	Black / Black

