FLOS

LIGHT SHADOW ADJUSTABLE TRIM 2 SPOTS OPTIC MEDIUM

Adjustable

Symmetric

Included Remote Electronic Without Class II

75 0,25

23° Medium

Mounting Lamps description Luminaire luminous flux Environment Notes Ceiling recessed Power LED 5,4W 560 Im 3000K CRI 90 Extreme Cut-off. See reference number Indoor Pre-installation frame not required.

OPTICAL

Aiming Light distribution symmetry Beam angle

ELECTRICAL

Transformer availability
Transformer mounting
Transformer type
Emergency
Insulation class

PHYSICAL

Recessed depth (mm)	
Weight (kg)	







Light Shadow Adjustable Trim 2 Spots Optic Medium

designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

🖉 03.9310.40 - 4211m	White / White
🗸 03.9310.14 - 4211m	Black / White
🖉 03.9312.40 - 427lm	White / Chrome
🚺 03.9312.14 - 427lm	Black / Chrome
🥖 03.9313.40 - 419lm	White / Matt Gold
🏉 03.9313.14 - 419lm	Black / Matt Gold
🕖 03.9311.40 - 414lm	White / Black
03.9311.14 - 414lm	Black / Black





FLOS

Light Shadow Adjustable Trim 2 Spots Optic Medium . Lamps



Power LED LED Socket: Special base Lamp type: Power LED



Light Shadow Adjustable Trim 2 Spots Optic Medium designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

03.9310.40 - 4211m	White / White
Ø3.9310.14 - 4211m	Black / White
alionali alioni	White / Chrome
🚺 03.9312.14 - 427lm	Black / Chrome
🥖 03.9313.40 - 419lm	White / Matt Gold
🏉 03.9313.14 - 419lm	Black / Matt Gold
🕖 03.9311.40 - 414lm	White / Black
🕖 03.9311.14 - 414lm	Black / Black

