FLOS

LIGHT SHADOW ADJUSTABLE TRIM 2 SPOTS OPTIC FLOOD

Included Remote Electronic Without Class II

75 0,25

Mounting Lamps description Luminaire luminous flux Environment Notes Ceiling recessed Power LED 5,4W 560 Im 3000K CRI 90 Extreme Cut-off. See reference number Indoor Pre-installation frame not required.

OPTICAL

AimingAdjustableLight distribution symmetrySymmetricBeam angle33° Flood

ELECTRICAL

Transformer availability
Transformer mounting
Transformer type
Emergency
Insulation class

PHYSICAL

Recessed depth (mm)	
Weight (kg)	







Light Shadow Adjustable Trim 2 Spots Optic Flood

designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

🕖 03.9315.40 - 420lm	White / White
Ø3.9315.14 - 420lm	Black / White
alionali alioni	White / Chrome
🚺 03.9317.14 - 430lm	Black / Chrome
🥖 03.9318.40 - 417lm	White / Matt Gold
🏉 03.9318.14 - 417lm	Black / Matt Gold
🕖 03.9316.40 - 408lm	White / Black
03.9316.14 - 408lm	Black / Black





FLOS

Light Shadow Adjustable Trim 2 Spots Optic Flood . Lamps



Power LED LED Socket: Special base Lamp type: Power LED



Light Shadow Adjustable Trim 2 Spots Optic Flood designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

03.9315.40 - 420lm	White / White
Ø3.9315.14 - 420lm	Black / White
🥥 03.9317.40 - 430lm	White / Chrome
🖉 03.9317.14 - 430lm	Black / Chrome
🥖 03.9318.40 - 417lm	White / Matt Gold
🏉 03.9318.14 - 417lm	Black / Matt Gold
● 03.9316.40 - 408lm	White / Black
03.9316.14 - 408lm	Black / Black

