

## **LIGHT SHADOW ADJUSTABLE TRIM 4 SPOTS OPTIC MEDIUM**

**Mounting** Ceiling recessed

Lamps descriptionPower LED 10,8W 1040 Im 2700K CRI 90Luminaire luminous fluxExtreme Cut-off. See reference number

**Environment** Indoor

**Notes** Pre-installation frame not required.

### **OPTICAL**

Aiming Adjustable
Light distribution symmetry Symmetric
Beam angle 23° Medium

#### **ELECTRICAL**

Transformer availability Included
Transformer mounting Remote
Transformer type Electronic
Emergency Without
Insulation class Class II

#### **PHYSICAL**

Recessed depth (mm) 75 Weight (kg) 0,34






## Light Shadow Adjustable Trim 4 Spots Optic Medium

designed by FLOS Architectural

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included.

03.9320.40 - 790lm	White / White
03.9320.14 - 790lm	Black / White
03.9322.40 - 801lm	White / Chrome
03.9322.14 - 801lm	Black / Chrome
<b>3.9323.40 - 786</b> lm	White / Matt Gold
<b>0</b> 3.9323.14 - 786lm	Black / Matt Gold
<b>3.9321.40 - 776lm</b>	White / Black
03.9321.14 - 776lm	Black / Black



### **CERTIFICATIONS**




















# Light Shadow Adjustable Trim 4 Spots Optic Medium . Lamps



**Power LED** 

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED




# Light Shadow Adjustable Trim 4 Spots Optic Medium

designed by FLOS Architectural

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included.

03.9320.40 - 790lm	White / White
03.9320.14 - 790lm	Black / White
03.9322.40 - 801lm	White / Chrome
03.9322.14 - 801lm	Black / Chrome
<b>3.9323.40 - 786</b> lm	White / Matt Gold
03.9323.14 - 786lm	Black / Matt Gold
<b>3.9321.40 - 776lm</b>	White / Black
03.9321.14 - 776lm	Black / Black



## **CERTIFICATIONS**















