## FLOS

## LIGHT SHADOW ADJUSTABLE NO TRIM 2 SPOTS OPTIC FLOOD

Mounting Lamps description Luminaire luminous flux Environment Notes Ceiling recessed Power LED 5,4W 560 Im 3000K CRI 90 Extreme Cut-off. See reference number Indoor It requires an pre-installation frame, to be ordered separately.

## OPTICAL

AimingAdjustableLight distribution symmetrySymmetricBeam angle33° Flood

## ELECTRICAL

Included
Remote
Electronic
Without
Class II

## PHYSICAL

Recessed depth (mm)	75
Weight (kg)	0,25




## Light Shadow Adjustable No Trim 2 Spots Optic Flood


designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

🖉 03.9415.40 - 420lm	White / White
🗸 03.9415.14 - 420lm	Black / White
alin 03.9417.40 - 430lm	White / Chrome
🕑 03.9417.14 - 430lm	Black / Chrome
🥖 03.9418.40 - 417lm	White / Matt Gold
🏉 03.9418.14 - 417lm	Black / Matt Gold
🕑 03.9416.40 - 408lm	White / Black
🕖 03.9416.14 - 408lm	Black / Black



# CERTIFICATIONS Image: Certification of the state o



## FLOS

## Light Shadow Adjustable No Trim 2 Spots Optic Flood . Accessories

## Mounting





08.0515.00

Pre-installation frame. Adjustable No Trim 2L

08.0059.90

## Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim preinstallation frames.

Light Shadow Adjustable No Trim 2 Spots Optic Flood . Lamps



Power LED LED Socket: Special base Lamp type: Power LED



## Light Shadow Adjustable No Trim 2 Spots Optic Flood designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

🖉 03.9415.40 - 420lm	White / White
Ø3.9415.14 - 420lm	Black / White
🥒 03.9417.40 - 430lm	White / Chrome
🖉 03.9417.14 - 430lm	Black / Chrome
🥖 03.9418.40 - 417lm	White / Matt Gold
🏉 03.9418.14 - 417lm	Black / Matt Gold
🥑 03.9416.40 - 408lm	White / Black
03.9416.14 - 408lm	Black / Black

