FLOS

LIGHT SHADOW ADJUSTABLE NO TRIM 4 SPOTS OPTIC MEDIUM

Adjustable

Symmetric

Included Remote Electronic Without Class II

75 0,34

23° Medium

Mounting Lamps description Luminaire luminous flux Environment Notes Ceiling recessed Power LED 10,8W 1120 lm 3000K CRI 90 Extreme Cut-off. See reference number Indoor It requires an pre-installation frame, to be ordered separately.

OPTICAL

Aiming Light distribution symmetry Beam angle

ELECTRICAL

Transformer availability
Transformer mounting
Transformer type
Emergency
Insulation class

PHYSICAL

Recessed depth (mm)	
Weight (kg)	





Light Shadow Adjustable No Trim 4 Spots Optic Medium


designed by FLOS Architectural

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included.

🖉 03.9430.40 - 843lm	White / White
Ø3.9430.14 - 843lm	Black / White
🖉 03.9432.40 - 855lm	White / Chrome
🖉 03.9432.14 - 855lm	Black / Chrome
🥖 03.9433.40 - 839lm	White / Matt Gold
🏉 03.9433.14 - 839lm	Black / Matt Gold
🟉 03.9431.40 - 828lm	White / Black
03.9431.14 - 828lm	Black / Black







FLOS

Light Shadow Adjustable No Trim 4 Spots Optic Medium . Accessories

Mounting





08.0516.00

Pre-installation frame. Adjustable No Trim 4L

08.0059.90

Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim preinstallation frames.

Light Shadow Adjustable No Trim 4 Spots Optic Medium . Lamps



Power LED LED Socket: Special base Lamp type: Power LED



designed by FLOS Architectural

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included.

🕖 03.9430.40 - 843lm	White / White
Ø3.9430.14 - 843lm	Black / White
🥒 03.9432.40 - 855lm	White / Chrome
🚺 03.9432.14 - 855lm	Black / Chrome
🌽 03.9433.40 - 839lm	White / Matt Gold
🏉 03.9433.14 - 839lm	Black / Matt Gold
🟉 03.9431.40 - 828lm	White / Black
03.9431.14 - 828lm	Black / Black

