

LIGHT SHADOW ADJUSTABLE NO TRIM 12 SPOTS OPTIC MEDIUM

Mounting Ceiling recessed

Lamps descriptionPower LED 32,4W 3120 lm 2700K CRI 90Luminaire luminous fluxExtreme Cut-off. See reference number

Environment Indoor

Notes It requires an pre-installation frame, to be ordered separately

OPTICAL

Aiming Adjustable
Light distribution symmetry Symmetric
Beam angle 23° Medium

ELECTRICAL

Transformer availability Included
Transformer mounting Remote
Transformer type Electronic
Emergency Without
Insulation class Class II

PHYSICAL

Recessed depth (mm) 75 Weight (kg) 0,66






Light Shadow Adjustable No Trim 12 Spots Optic Medium

designed by FLOS Architectural

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included.

03.9460.40 - 2369lm White / White 03.9460.14 - 2369lm Black / White a 03.9462.40 - 2402lm White / Chrome 03.9462.14 - 2402lm Black / Chrome 03.9463.40 - 2358lm White / Matt Gold 03.9463.14 - 2358lm Black / Matt Gold **d** 03.9461.40 - 2327lm White / Black 03.9461.14 - 2327lm Black / Black



CERTIFICATIONS




















Light Shadow Adjustable No Trim 12 Spots Optic Medium . Accessories

Mounting





08.0518.00

08.0059.90

Pre-installation frame. Adjustable No Trim 12L Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim preinstallation frames.

Light Shadow Adjustable No Trim 12 Spots Optic Medium . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED




Light Shadow Adjustable No Trim 12 Spots Optic Medium

designed by FLOS Architectural

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included.

0 00 0440 40 00401	
03.9460.40 - 2369lm	White / White
0 3.9460.14 - 2369lm	Black / White
03.9462.40 - 2402lm	White / Chrome
03.9462.14 - 2402lm	Black / Chrome
o3.9463.40 - 2358lm	White / Matt Gold
O3.9463.14 - 2358lm	Black / Matt Gold
■ 03.9461.40 - 2327lm	White / Black
03.9461.14 - 2327lm	Black / Black



CERTIFICATIONS















