FLOS

LIGHT SHADOW ADJUSTABLE NO TRIM 12 SPOTS OPTIC MEDIUM

Adjustable

Symmetric

Included

Remote

Electronic

Without

Class II

23° Medium

Mounting Lamps description Luminaire luminous flux Environment Notes Ceiling recessed Power LED 32,4W 3360 Im 3000K CRI 90 Extreme Cut-off. See reference number Indoor It requires an pre-installation frame, to be ordered separately.

OPTICAL

Aiming Light distribution symmetry Beam angle

ELECTRICAL

Transformer availability Transformer mounting Transformer type Emergency Insulation class

PHYSICAL

Recessed depth (mm)	
Weight (kg)	


75 0,66





Light Shadow Adjustable No Trim 12 Spots Optic Medium designed by FLOS Architectural

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included.

🖉 03.9470.40 - 2528lm	White / White
Ø3.9470.14 - 2528lm	Black / White
alional di constructione de la construcción de la c	White / Chrome
🔵 03.9472.14 - 2564lm	Black / Chrome
🥖 03.9473.40 - 2517lm	White / Matt Gold
🏉 03.9473.14 - 2517lm	Black / Matt Gold
🟉 03.9471.40 - 2484lm	White / Black
03.9471.14 - 2484lm	Black / Black







FLOS

Light Shadow Adjustable No Trim 12 Spots Optic Medium . Accessories

Mounting



Light Shadow Adjustable No Trim 12 Spots Optic Medium . Lamps



Power LED LED Socket: Special base Lamp type: Power LED



designed by FLOS Architectural

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included.

03.9470.40 - 2528lm	White / White
Ø3.9470.14 - 2528lm	Black / White
🥒 03.9472.40 - 2564lm	White / Chrome
🖉 03.9472.14 - 2564lm	Black / Chrome
🥖 03.9473.40 - 2517lm	White / Matt Gold
🏉 03.9473.14 - 2517lm	Black / Matt Gold
🟉 03.9471.40 - 2484lm	White / Black
🕖 03.9471.14 - 2484lm	Black / Black

