

PURE I DOWNLIGHT

Number of heads

Mounting Ceiling recessed

Lamps description CDM-TM PGJ5 Max 35W

Voltage (V) 220/240 Environment Indoor

Notes To be completed with installation frame. Available as

accessory element. Must be ordered separately.

OPTICAL

Light controller descriptionProtection glassAimingAdjustableLight distribution symmetrySymmetricBeam angle10° Spot

ELECTRICAL

Control gear availability

Control gear mounting

Emergency

Insulation class

Separate item
Remote
Without
Class II

PHYSICAL

Cutout diameter (mm) 135
Spot diameter (mm) 86
Construction material Alum

Construction material Aluminium Weight (kg) 0,96






Pure I Downlight designed by Knud Holscher

Metal halide lamp recessed downlight. Remote control gear not included

09.1620.30 White 09.1620.02 Grey 09.1620.14 Black



CERTIFICATIONS




















Flos.architectural@flos.com www.flos.com



Pure I Downlight . Accessories

Optical









Pure I Downlight designed by Knud Holscher

08.8166.14

Holding ring

Elliptical lens

08.8163.68

Elliptical light distribution lens in 4 mm thick tempered glass. 08.8169.14

Honeycomb


"Honeycomb" anti-glare screen: in thin, blackpainted aluminium

Metal halide lamp recessed downlight. Remote control gear not included









08.8160.64.OD

Blue filter

Blue filter

08.8160.65.OD

Sky blue filter


Sky blue filter



08.8160.66.OD

Amber filter

Amber filter

























GWT

850°

08.8160.67.OD

Red filter

Red filter

08.8160.98.OD


U.V. filter

U.V. filter

08.8160.68

I.R. filter

I.R. filter



Flos.architectural@flos.com www.flos.com

Pure I Downlight . Accessories









08.8160.69

08.8160.CL Cold light filter

Pure I Downlight designed by Knud Holscher

Hot Light

Hot Light

Cold light filter

Daylight filter

Daylight filter

08.8160.DL

Metal halide lamp recessed downlight. Remote control gear not included










08.8160.ND

08.8175.68

glass.



08.8232.30




Neodimium









Flood lens made in press

Pure I Pro external ring accessory

Pure I Pro external ring accessory. Only for halogen and halide lamps, consult for LED version

CERTIFICATIONS

























Pure I Downlight . Accessories

Mounting









08.8152.00

Installation Frame For No Trim

Installation frame for Pure I Downlight No Trim.

HOW TO ORDER

08.8149.30

08.8149.02

08.8149.14

Installation Frame For Trim

Installation frame for Pure I Downlight Trim.

Pure I Downlight designed by Knud Holscher


Metal halide lamp recessed downlight. Remote control gear not included

09.1620.30 White 09.1620.02 Grey 09.1620.14 Black

Pure I Downlight . Lamps







60.6149 60.6151

CDM-Tm

Lamp Watt:
20 W 35 W

Lamp category:Lamp category:Metal halideMetal halideSocket:Socket:PGJ5PGJ5

Color temperature (K): Color temperature (K):

3000 °K 3000 °K

Catalog reference: Catalog reference:

 60.6149
 60.6151

 Lamp type:
 Lamp type:

 CDM-Tm
 CDM-Tm

CERTIFICATIONS




















Flos.architectural@flos.com www.flos.com