

### **PURE I DOWNLIGHT**

Number of heads

**Mounting** Ceiling recessed

Lamps description CDM-TM PGJ5 Max 35W

Voltage (V) 220/240 Environment Indoor

Notes To be completed with installation frame. Available as

accessory element. Must be ordered separately.

### **OPTICAL**

Light controller descriptionProtection glassAimingAdjustableLight distribution symmetrySymmetricBeam angle24° Flood

### **ELECTRICAL**

Control gear availability

Control gear mounting

Emergency

Insulation class

Separate item
Remote
Without
Class II

### **PHYSICAL**

Cutout diameter (mm) 135 Spot diameter (mm) 86

Construction material Aluminium Weight (kg) 0,96






Pure I Downlight designed by Knud Holscher

Metal halide lamp recessed downlight. Remote control gear not included

09.1621.02 White
09.1621.02 Grey
09.1621.14 Black



### **CERTIFICATIONS**




















Flos.architectural@flos.com www.flos.com



# Pure I Downlight . Accessories

### **Optical**









08.8166.14

Holding ring

08.8163.68 **Elliptical lens** 

08.8169.14

Honeycomb

"Honeycomb" anti-glare screen: in thin, blackpainted aluminium

Metal halide lamp recessed downlight. Remote control gear not included





Elliptical light distribution lens in 4 mm thick tempered glass.














08.8160.64.OD

Blue filter

Blue filter

08.8160.65.OD

Sky blue filter

Sky blue filter

# 08.8160.66.OD

**Amber filter** 

Amber filter









# **CERTIFICATIONS**









ΙP

20







08.8160.67.OD

Red filter

Red filter

08.8160.98.OD


U.V. filter

U.V. filter

08.8160.68

I.R. filter


I.R. filter



Flos.architectural@flos.com www.flos.com

Pure I Downlight . Accessories









08.8160.69

Hot Light

**Hot Light** Cold light filter

Cold light filter

08.8160.CL

08.8160.DL

**Daylight filter** 

Daylight filter

Pure I Downlight designed by Knud Holscher

Metal halide lamp recessed downlight. Remote control gear not included









Grey

09.1621.14

Black

White



08.8160.ND




Flood lens





08.8232.02

08.8232.14



ø135

### Neodimium

Flood lens made in press glass.

### Pure I Pro external ring accessory

Pure I Pro external ring accessory. Only for halogen and halide lamps, consult for LED version

# **CERTIFICATIONS**






















Flos.architectural@flos.com www.flos.com



# Pure I Downlight . Accessories

## Mounting


08.8152.00

No Trim



Installation Frame For

Installation frame for Pure I Downlight No Trim.





**HOW TO ORDER** 



08.8149.30

08.8149.02

08.8149.14

Pure I Downlight designed by Knud Holscher

Metal halide lamp recessed downlight. Remote control gear not included

**Installation Frame For Trim** 

Installation frame for Pure I Downlight Trim.



# Pure I Downlight . Lamps





60.6149 60.6151 CDM-Tm CDM-Tm Lamp Watt: Lamp Watt: 20 W 35 W


Lamp category: Lamp category: Metal halide Metal halide Socket: Socket: PGI5 PG<sub>[5</sub>

Color temperature (K): Color temperature (K):

3000 °K 3000 °K

Catalog reference: Catalog reference:

60.6149 60.6151 Lamp type: Lamp type: CDM-Tm CDM-Tm



# **CERTIFICATIONS**




















Flos.architectural@flos.com www.flos.com