FLOS

PURE I DOWNLIGHT DALI

Number of heads

Mounting Ceiling recessed

Lamps descriptionPhosphor LED 11,9W 1057 Im 3000K CRI 98Luminaire luminous fluxExtreme Cut-off. See reference number

Voltage (V) 220/240 Environment Indoor

Notes To be completed with installation frame. Available as

accessory element. Must be ordered separately.

OPTICAL

Light controller descriptionReflectorAimingAdjustableLight distribution symmetrySymmetricBeam angle23° Medium

ELECTRICAL

Transformer availability Included
Transformer mounting Remote

Transformer type Electronic dimmable dali

EmergencyWithoutInsulation classClass II

PHYSICAL

Cutout diameter (mm) 135 Spot diameter (mm) 86

Construction material Aluminium
Weight (kg) 0,96






Pure I Downlight Dali designed by Knud Holscher

LED recessed downlight. Phosphor LED module integrated. Remote electronic transformer 220/240V included.

09.1630.30CDA - 725lm White
09.1630.02CDA - 725lm Grey
09.1630.14CDA - 725lm Black



CERTIFICATIONS




















Flos.architectural@flos.com www.flos.com



Pure I Downlight Dali . Accessories

Optical









08.8166.14

Holding ring

08.8163.68 **Elliptical lens**

08.8169.14

Honeycomb

"Honeycomb" anti-glare screen: in thin, blackpainted aluminium sheets.

Pure I Downlight Dali designed by Knud Holscher

LED recessed downlight. Phosphor LED module integrated. Remote electronic transformer 220/240V included.






09.1630.30CDA - 725lm White 09.1630.02CDA - 725lm Grey 09.1630.14CDA - 725lm Black





Elliptical light distribution lens in 4 mm thick tempered glass.





ø86 ø142

08.8160.64.OD

Blue filter

Blue filter

08.8160.65.OD

Sky blue filter

Sky blue filter

08.8160.98.OD

U.V. filter

U.V. filter

08.8160.66.OD

Amber filter

Amber filter













360°





ΙP


20



08.8160.68

I.R. filter

I.R. filter



08.8160.67.OD

Red filter

Red filter

Flos.architectural@flos.com www.flos.com



Pure I Downlight Dali . Accessories









08.8160.69

Hot Light

Hot Light

08.8160.CL

Cold light filter

Cold light filter

08.8160.DL

Daylight filter

Daylight filter


Pure I Downlight Dali designed by Knud Holscher

LED recessed downlight. Phosphor LED module integrated. Remote electronic transformer 220/240V included.











Neodimium



Flood lens

Flood lens made in press glass.








Pure I Pro external ring accessory

Pure I Pro external ring accessory. Only for halogen and halide lamps, consult for LED version



CERTIFICATIONS





















Flos.architectural@flos.com www.flos.com



Pure I Downlight Dali . Accessories

Mounting









08.8152.00

Installation Frame For No Trim

Installation frame for Pure I Downlight No Trim.

HOW TO ORDER

08.8149.30

08.8149.02

08.8149.14

Installation Frame For Trim

Installation frame for Pure I Downlight Trim.

Pure I Downlight Dali designed by Knud Holscher

LED recessed downlight. Phosphor LED module integrated. Remote electronic transformer 220/240V included.

09.1630.30CDA - 725lm White
09.1630.02CDA - 725lm Grey
09.1630.14CDA - 725lm Black

Ø135 30 max Ø86 Ø142

Pure I Downlight Dali . Lamps



Phosphor LED Lamp category:

LED

Lamp type:

Phosphor LED

CERTIFICATIONS




















Flos.architectural@flos.com www.flos.com