FLOS

PURE I DOWNLIGHT

Number of heads

Mounting Ceiling recessed

Lamps descriptionPhosphor LED 11,9W 1057 Im 3000K CRI 98Luminaire luminous fluxExtreme Cut-off. See reference number

Voltage (V) 220/240 Environment Indoor

Notes To be completed with installation frame. Available as

accessory element. Must be ordered separately.

OPTICAL

Light controller descriptionReflectorAimingAdjustableLight distribution symmetrySymmetricBeam angle51° Wide Flood

ELECTRICAL

Transformer availability Included
Transformer mounting Remote
Transformer type Electronic
Emergency Without
Insulation class Class II

PHYSICAL

Cutout diameter (mm) 135 Spot diameter (mm) 86 Construction material Alui

Construction material Aluminium
Weight (kg) 0,96






Pure I Downlight designed by Knud Holscher

LED recessed downlight. Phosphor LED module integrated. Remote electronic transformer 220/240V included.

09.1632.30C - 759lm White 09.1632.02C - 759lm Grey 09.1632.14C - 759lm Black



CERTIFICATIONS






















Pure I Downlight . Accessories

Optical









08.8166.14

Holding ring

08.8163.68

Elliptical lens

Elliptical light distribution lens in 4 mm thick tempered glass.

08.8169.14

Honeycomb

"Honeycomb" anti-glare screen: in thin, blackpainted aluminium sheets. Pure I Downlight designed by Knud Holscher


LED recessed downlight. Phosphor LED module integrated. Remote electronic transformer 220/240V included.

09.1632.30C - 759lm White 09.1632.02C - 759lm Grey 09.1632.14C - 759lm Black









08.8160.64.OD

Blue filter

Blue filter

08.8160.65.OD


Sky blue filter

Sky blue filter

08.8160.66.OD

Amber filter

Amber filter



















08.8160.98.OD

U.V. filter


U.V. filter

08.8160.68

I.R. filter

I.R. filter





08.8160.67.OD

Red filter

Red filter


Flos.architectural@flos.com

www.flos.com

Pure I Downlight . Accessories









08.8160.69

Hot Light

Hot Light

08.8160.CL

Cold light filter

Cold light filter

08.8160.DL

Daylight filter

Daylight filter

Pure I Downlight designed by Knud Holscher

LED recessed downlight. Phosphor LED module integrated. Remote electronic transformer 220/240V included.







09.1632.30C - 759lm White 09.1632.02C - 759lm Grey 09.1632.14C - 759lm Black

08.8160.ND

Neodimium

08.8175.68

Flood lens

Flood lens made in press glass.






08.8232.02 08.8232.14

Pure I Pro external ring accessory

Pure I Pro external ring accessory. Only for halogen and halide lamps, consult for LED version



CERTIFICATIONS





















Flos.architectural@flos.com www.flos.com



Pure I Downlight . Accessories

Mounting







08.8152.00

Installation Frame For No Trim

Installation frame for Pure I Downlight No Trim.

HOW TO ORDER

08.8149.30

08.8149.02

08.8149.14

Installation Frame For Trim


Installation frame for Pure I Downlight Trim.



Pure I Downlight designed by Knud Holscher

LED recessed downlight. Phosphor LED module integrated. Remote electronic transformer 220/240V included.

09.1632.30C - 759lm White
09.1632.02C - 759lm Grey
09.1632.14C - 759lm Black



Pure I Downlight . Lamps



Phosphor LED
Lamp category:
LED

Lamp type: Phosphor LED

CERTIFICATIONS




















Flos.architectural@flos.com www.flos.com