

PURE I DOWNLIGHT I-10V

Number of heads

Mounting Ceiling recessed

Lamps descriptionPhosphor LED 11,9W 1057 Im 3000K CRI 98Luminaire luminous fluxExtreme Cut-off. See reference number

Voltage (V) 220/240 Environment Indoor

Notes To be completed with installation frame. Available as

accessory element. Must be ordered separately.

OPTICAL

Light controller descriptionReflectorAimingAdjustableLight distribution symmetrySymmetricBeam angle51° Wide Flood

ELECTRICAL

Transformer availability Included
Transformer mounting Remote

Transformer type Electronic dimmable I-10V

EmergencyWithoutInsulation classClass II

PHYSICAL

Cutout diameter (mm) 135 Spot diameter (mm) 86

Construction material Aluminium
Weight (kg) 0,96






Pure I Downlight I-10V designed by Knud Holscher

LED recessed downlight. Phosphor LED module integrated. Remote electronic transformer 220/240V included.

09.1632.30C1V - 759lm White
09.1632.02C1V - 759lm Grey
09.1632.14C1V - 759lm Black



CERTIFICATIONS

















Flos.architectural@flos.com www.flos.com



Pure I Downlight I-I0V. Accessories

Optical









08.8166.14

Holding ring

08.8163.68 **Elliptical lens**

Elliptical light distribution lens in 4 mm thick tempered glass. 08.8169.14

Honeycomb

"Honeycomb" anti-glare screen: in thin, blackpainted aluminium sheets.

Pure I Downlight I-I0V designed by Knud Holscher


LED recessed downlight. Phosphor LED module integrated. Remote electronic transformer 220/240V included.

09.1632.30CIV - 759lm White 09.1632.02CIV - 759lm Grey 09.1632.14CIV - 759lm Black









08.8160.64.OD

Blue filter

Blue filter

08.8160.65.OD


Sky blue filter

Sky blue filter

08.8160.66.OD

Amber filter

Amber filter









CERTIFICATIONS



60°







08.8160.98.OD U.V. filter

U.V. filter

08.8160.68

I.R. filter

I.R. filter





08.8160.67.OD

Red filter

Red filter

Flos.architectural@flos.com


www.flos.com



Pure I Downlight I-I0V. Accessories









08.8160.69

Hot Light

Hot Light

08.8160.CL

Cold light filter

Cold light filter

08.8160.DL

Daylight filter

Daylight filter

Pure I Downlight I-I0V designed by Knud Holscher

LED recessed downlight. Phosphor LED module integrated. Remote electronic transformer 220/240V included.







09.1632.30CIV - 759lm White 09.1632.02CIV - 759lm Grey

09.1632.14CIV - 759lm Black











ø86

ø142

08.8160.ND

Neodimium

08.8175.68

Flood lens

Flood lens made in press glass.



08.8232.30

Pure I Pro external ring accessory

Pure I Pro external ring accessory. Only for halogen and halide lamps, consult for LED version

CERTIFICATIONS









45










Flos.architectural@flos.com www.flos.com



Pure I Downlight I-I0V. Accessories

Mounting







08.8152.00

Installation Frame For No Trim

Installation frame for Pure I Downlight No Trim.

HOW TO ORDER

08.8149.30

08.8149.02

08.8149.14

Installation Frame For Trim


Installation frame for Pure I Downlight Trim.



Pure I Downlight I-10V designed by Knud Holscher

LED recessed downlight. Phosphor LED module integrated. Remote electronic transformer 220/240V included.

09.1632.30CIV - 759lm White
09.1632.02CIV - 759lm Grey
09.1632.14CIV - 759lm Black



Pure I Downlight I-I0V . Lamps



Phosphor LED
Lamp category:
LED

Lamp type: Phosphor LED

CERTIFICATIONS

















Flos.architectural@flos.com www.flos.com