FLOS

PURE I DOWNLIGHT I-10V

Number of heads

Mounting Ceiling recessed

Lamps descriptionPhosphor LED 13,6W 1490 lm 3000K CRI 80Luminaire luminous fluxExtreme Cut-off. See reference number

Voltage (V) 220/240 Environment Indoor

Notes To be completed with installation frame. Available as

accessory element. Must be ordered separately.

OPTICAL

Light controller descriptionReflectorAimingAdjustableLight distribution symmetrySymmetricBeam angle46° Flood

ELECTRICAL

Transformer availability Included
Transformer mounting Remote

Transformer type Electronic dimmable I-10V

EmergencyWithoutInsulation classClass II

PHYSICAL

Cutout diameter (mm) 135 Spot diameter (mm) 86

Construction material Aluminium
Weight (kg) 0,96






Pure I Downlight I-10V designed by Knud Holscher

LED recessed downlight. Phosphor LED module integrated. Remote electronic transformer 220/240V included.

09.1636.30CIV - 1107lm White
09.1636.02CIV - 1107lm Grey
09.1636.14CIV - 1107lm Black



CERTIFICATIONS






















Pure I Downlight I-I0V. Accessories

Optical









08.8166.14

Holding ring

08.8163.68 Elliptical lens

Elliptical light distribution lens in 4 mm thick tempered glass. 08.8169.14

Honeycomb

"Honeycomb" anti-glare screen: in thin, blackpainted aluminium sheets.

Pure I Downlight I-I0V designed by Knud Holscher

LED recessed downlight. Phosphor LED module integrated. Remote electronic transformer 220/240V included.


09.1636.30CIV - 1107lm White

09.1636.02CIV - 1107lm Grey 09.1636.14C1V - 1107lm Black









08.8160.64.OD

Blue filter

Blue filter

08.8160.65.OD


Sky blue filter

Sky blue filter

08.8160.66.OD

Amber filter

Amber filter

























08.8160.67.OD

Red filter

Red filter

08.8160.98.OD


U.V. filter

U.V. filter

08.8160.68

I.R. filter

I.R. filter



Flos.architectural@flos.com www.flos.com



Pure I Downlight I-I0V. Accessories









08.8160.69

Hot Light

Hot Light

08.8160.CL

Cold light filter

Cold light filter

08.8160.DL

Daylight filter

Daylight filter


Pure I Downlight I-I0V designed by Knud Holscher

LED recessed downlight. Phosphor LED module integrated. Remote electronic transformer 220/240V included.









09.1636.14C1V - 1107lm Black











08.8175.68

Flood lens

glass.




08.8232.30



08.8232.02



08.8232.14



Flood lens made in press

Pure I Pro external ring accessory

Pure I Pro external ring accessory. Only for halogen and halide lamps, consult for LED version





















CERTIFICATIONS



Pure I Downlight I-I0V. Accessories

Mounting









08.8152.00

Installation Frame For No Trim

Installation frame for Pure I Downlight No Trim.

HOW TO ORDER

08.8149.30

08.8149.02

08.8149.14

Installation Frame For Trim

Installation frame for Pure I Downlight Trim.

Pure I Downlight I-10V designed by Knud Holscher

LED recessed downlight. Phosphor LED module integrated. Remote electronic transformer 220/240V included.

09.1636.30CIV - 1107lm White
09.1636.02CIV - 1107lm Grey
09.1636.14CIV - 1107lm Black

886 Ø142

Pure I Downlight I-10V . Lamps



Phosphor LED
Lamp category:
LED

Lamp type:

Phosphor LED

CERTIFICATIONS




















Flos.architectural@flos.com www.flos.com