

PURE 2 DOWNLIGHT

Number of heads

Mounting Ceiling recessed

Lamps description QT-12 GY6.35 Max 100W

Voltage (V) 12
Environment Indoor

Notes To be completed with installation frame. Available as

accessory element. Must be ordered separately.

OPTICAL

Light controller descriptionProtection glassAimingAdjustableLight distribution symmetrySymmetricBeam angle6° Super Spot

ELECTRICAL

Transformer availability
Separate item
Transformer mounting
Remote
Without
Insulation class
Class III

PHYSICAL

Cutout diameter (mm) 165
Spot diameter (mm) 113
Construction material Aluminium
Weight (kg) 1,43






Pure 2 Downlight designed by Knud Holscher

12V halogen lamp recessed downlight. Remote transformer not included

09.1712.30	White
09.1712.02	Grey
09.1712.14	Black



CERTIFICATIONS




















Flos.architectural@flos.com www.flos.com



Pure 2 Downlight . Accessories

Optical









08.8167.14

Holding ring

Holding ring

08.8170.14

Honeycomb

"Honeycomb" anti-glare screen: in thin, blackpainted aluminium sheets.

08.8161.64.OD

Blue filter

Blue filter

Pure 2 Downlight designed by Knud Holscher


12V halogen lamp recessed downlight. Remote transformer not included

09.1712.30	White
09.1712.02	Grey
09.1712.14	Black









08.8161.65.OD

Sky blue filter

Sky blue filter

08.8161.66.OD

Amber filter

Amber filter

08.8161.68

I.R. filter

I.R. filter

08.8161.67.OD

Red filter

Red filter











60°



360°







GWT 850°



08.8161.98.OD

U.V. filter


U.V. filter



08.8161.CL

Cold light filter

Cold light filter



Flos.architectural@flos.com www.flos.com

Pure 2 Downlight . Accessories









08.8161.DL

Daylight filter

Daylight filter

08.8164.68

Elliptical light

distribution lens

Elliptical light distribution lens in 4mm thick tempered glass.

12V halogen lamp recessed downlight. Remote transformer not included

09.1712.30 White 09.1712.02 Grey 09.1712.14 Black









Hot Light

Hot Light

08.8176.68

08.8161.ND

Neodimium

Neodimium

Flood lens


Flood lens made in press glass.






08.8233.02

08.8233.14



Pure 2 Pro external ring accessory.



CERTIFICATIONS




















08.8234.02

08.8234.14

Pure Downlight 2 Wall-Washer external ring accessory
Pure Downlight 2 Wall-Washer
external ring accessory.




Flos.architectural@flos.com www.flos.com



Pure 2 Downlight . Accessories

Mounting









Pure 2 Downlight designed by Knud Holscher

12V halogen lamp recessed downlight. Remote transformer not included

White 09.1712.30 09.1712.02 Grey 09.1712.14 Black

08.8153.00

Installation Frame for No Trim

Installation frame for Pure 2 Downlight No Trim.

HOW TO ORDER

Installation Frame for Trim

08.8150.30

08.8150.02

08.8150.14

Installation frame for Pure 2 Downlight Trim.

Pure 2 Downlight . Lamps













ø113 ø180



30

135

20









ΙP 20

35 W Lamp category: Halogen low voltage Socket:

60.6300

QT-12

Lamp Watt:

GY6.35 Color temperature (K): 3000 °K

Catalog reference:

60.6300 Lamp type: QT-12

60.6303 QT-12 Lamp Watt: 50 W

Lamp category: Halogen low voltage

Socket: GY6.35

Color temperature (K):

3000 °K

Catalog reference:

60.6303 Lamp type: QT-12

60.6304 QT-12

Lamp Watt: 75 W

Lamp category: Halogen low voltage


Socket: GY6.35

Color temperature (K):

3000 °K

Catalog reference: 60.6304

Lamp type: QT-12



Flos.architectural@flos.com www.flos.com

Pure 2 Downlight . Lamps





60.6305 QT-12

Lamp Watt: 90 W

Lamp category: Halogen low voltage

Socket: GY6.35

Color temperature (K):

3000 °K

Catalog reference:

60.6305 Lamp type: QT-12

60.6306

QT-12

Lamp Watt:

100 W

Lamp category: Halogen low voltage

Socket: GY6.35

Color temperature (K):

3000 °K

Catalog reference:

60.6306

Lamp type:


QT-12



Pure 2 Downlight designed by Knud Holscher

12V halogen lamp recessed downlight. Remote transformer not included

09.1712.30 White 09.1712.02 Grey 09.1712.14 Black



CERTIFICATIONS

















