

PURE 2 DOWNLIGHT

Number of heads

Mounting Ceiling recessed

Lamps description QT-12 GY6.35 Max 100W

Voltage (V) 12 Environment Indoor

Notes To be completed with installation frame. Available as

accessory element. Must be ordered separately.

OPTICAL

Light controller descriptionProtection glassAimingAdjustableLight distribution symmetrySymmetricBeam angle10° Spot

ELECTRICAL

Transformer availability

Separate item
Transformer mounting

Remote

Without
Insulation class

Class III

PHYSICAL

Cutout diameter (mm) 165
Spot diameter (mm) 113
Construction material Aluminium
Weight (kg) 1,43






Pure 2 Downlight designed by Knud Holscher

12V halogen lamp recessed downlight. Remote transformer not included

09.1713.30	White
09.1713.02	Grey
09.1713.14	Black



CERTIFICATIONS




















Flos.architectural@flos.com www.flos.com



Pure 2 Downlight . Accessories

Optical









08.8167.14

Holding ring

Holding ring

08.8170.14

Honeycomb

"Honeycomb" anti-glare screen: in thin, blackpainted aluminium sheets.

08.8161.64.OD

Blue filter

Blue filter

Pure 2 Downlight designed by Knud Holscher


12V halogen lamp recessed downlight. Remote transformer not included

09.1713.30 White 09.1713.02 Grey 09.1713.14 Black









08.8161.65.OD

Sky blue filter

Sky blue filter

08.8161.66.OD

Amber filter

Amber filter

08.8161.67.OD

Red filter

Red filter





60°



360°





ΙP

20



U.V. filter

U.V. filter








08.8161.CL

Cold light filter

Cold light filter



08.8161.98.OD

08.8161.68

I.R. filter

I.R. filter

Flos.architectural@flos.com www.flos.com

Pure 2 Downlight . Accessories









08.8161.DL

Daylight filter

Daylight filter

08.8164.68

Elliptical light distribution lens

Elliptical light distribution lens in 4mm thick tempered glass.

designed by Knud Holscher 12V halogen lamp recessed downlight. Remote transformer not included


09.1713.30 White 09.1713.02 Grey

09.1713.14









08.8161.69

Hot Light

Hot Light

08.8176.68

08.8161.ND

Neodimium

Neodimium

Flood lens

Flood lens made in press glass.




08.8233.02

08.8233.14

Pure 2 Pro external ring accessory

Pure 2 Pro external ring accessory.



CERTIFICATIONS







Black












08.8234.30

08.8234.02

08.8234.14

Pure Downlight 2 Wall-Washer external ring accessory
Pure Downlight 2 Wall-Washer
external ring accessory.






Pure 2 Downlight . Accessories

Mounting









Pure 2 Downlight designed by Knud Holscher

12V halogen lamp recessed downlight. Remote transformer not included

White
Grey
Black

08.8153.00

Installation Frame for No Trim

Installation frame for Pure 2 Downlight No Trim.

HOW TO ORDER

Installation Frame for Trim

08.8150.30

08.8150.02

08.8150.14

Installation frame for Pure 2 Downlight Trim.

Pure 2 Downlight . Lamps











60°







135

20



ø113 ø180



35 W Lamp category: Halogen low voltage Socket:

GY6.35 Color temperature (K):

60.6300 Lamp type:

QT-12

60.6300

QT-12

Lamp Watt:

3000 °K **Catalog reference:**

3000 °K Catalog reference: 60.6303

60.6303

QT-12

50 W

Socket:

GY6.35

Lamp Watt:

Lamp category:

Halogen low voltage

Color temperature (K):

Lamp type: QT-12



QT-12 Lamp Watt: 75 W


Lamp category: Halogen low voltage

Socket: GY6.35

Color temperature (K): 3000 °K

Catalog reference: 60.6304

Lamp type: QT-12



Flos.architectural@flos.com www.flos.com

Pure 2 Downlight . Lamps





60.6305 QT-12

Lamp Watt: 90 W

Lamp category: Halogen low voltage

Socket: GY6.35

Color temperature (K):

3000 °K

Catalog reference:

60.6305 Lamp type: QT-12

60.6306 QT-12

Lamp Watt: 100 W

Lamp category: Halogen low voltage

Socket: GY6.35

Color temperature (K):

3000 °K

Catalog reference:


60.6306 Lamp type: QT-12



Pure 2 Downlight designed by Knud Holscher

12V halogen lamp recessed downlight. Remote transformer not included

09.1713.30 White 09.1713.02 Grey 09.1713.14 Black



CERTIFICATIONS


















ΙP

20