

PURE 2 DOWNLIGHT

Number of heads

Mounting Ceiling recessed

Lamps description QT-12 GY6.35 Max 100W

Voltage (V) 12 Environment Indoor

Notes To be completed with installation frame. Available as

accessory element. Must be ordered separately.

OPTICAL

Light controller descriptionProtection glassAimingAdjustableLight distribution symmetrySymmetricBeam angle21° Flood

ELECTRICAL

Transformer availability

Separate item
Transformer mounting

Remote
Without
Insulation class

Class III

PHYSICAL

Cutout diameter (mm) 165
Spot diameter (mm) 113
Construction material Aluminium
Weight (kg) 1,43






Pure 2 Downlight designed by Knud Holscher

12V halogen lamp recessed downlight. Remote transformer not included

09.1714.30	White
09.1714.02	Grey
09.1714.14	Black



CERTIFICATIONS




















Flos.architectural@flos.com www.flos.com



Pure 2 Downlight . Accessories

Optical









08.8167.14

Holding ring

Holding ring

08.8170.14

Honeycomb

"Honeycomb" anti-glare screen: in thin, blackpainted aluminium sheets.

08.8161.64.OD

Blue filter

Blue filter

Pure 2 Downlight designed by Knud Holscher


12V halogen lamp recessed downlight. Remote transformer not included

09.1714.30	White
09.1714.02	Grey
09.1714.14	Black









08.8161.65.OD

Sky blue filter

Sky blue filter

08.8161.66.OD

Amber filter

Amber filter

08.8161.67.OD

Red filter

Red filter























www.flos.com



08.8161.98.OD

U.V. filter

U.V. filter

08.8161.68


I.R. filter

I.R. filter

08.8161.CL

Cold light filter

Cold light filter



Flos.architectural@flos.com

Pure 2 Downlight . Accessories









08.8161.DL

Daylight filter

Daylight filter

08.8161.ND

Neodimium

Neodimium

08.8164.68

Elliptical light distribution lens

Elliptical light distribution lens in 4mm thick tempered glass.

designed by Knud Holscher

12V halogen lamp recessed downlight. Remote transformer not included

09.1714.30 White 09.1714.02 Grey 09.1714.14 Black





08.8161.69

Hot Light

Hot Light

08.8176.68

Flood lens

Flood lens made in press glass.






08.8233.02 08.8233.14

Pure 2 Pro external ring accessory

Pure 2 Pro external ring accessory.



CERTIFICATIONS




















08.8234.30

08.8234.02

08.8234.14

Pure Downlight 2 Wall-Washer external ring accessory
Pure Downlight 2 Wall-Washer
external ring accessory.






Pure 2 Downlight . Accessories

Mounting









HOW TO ORDER

Pure 2 Downlight designed by Knud Holscher

Installation Frame for No Trim

08.8153.00

Installation frame for Pure 2 Downlight No Trim.

08.8150.02

08.8150.30

08.8150.14

Installation Frame for Trim

Installation frame for Pure 2 Downlight Trim.

12V halogen lamp recessed downlight. Remote transformer not included


White 09.1714.30 09.1714.02 Grey 09.1714.14 Black

Pure 2 Downlight . Lamps









QT-12 Lamp Watt:

60.6300

GY6.35

35 W Lamp category:

Halogen low voltage Socket:

Color temperature (K):

3000 °K

Catalog reference: 60.6300

Lamp type: QT-12

60.6303 QT-12

Lamp Watt:

50 W

Lamp category: Halogen low voltage

Socket: GY6.35

Color temperature (K):

3000 °K

Catalog reference:

60.6303

Lamp type: QT-12

60.6304

QT-12

Lamp Watt:

75 W

Lamp category:

Halogen low voltage

Socket: GY6.35

Color temperature (K):

3000 °K

Catalog reference:

60.6304

Lamp type:

QT-12



CERTIFICATIONS




















Flos.architectural@flos.com www.flos.com



Pure 2 Downlight . Lamps





60.6306

QT-12

100 W

Lamp Watt:

Lamp category:

Halogen low voltage

60.6305 **QT-12**

Lamp Watt: 90 ₩

Lamp category:

Halogen low voltage

Socket:Socket:GY6.35GY6.35

Color temperature (K): Color temperature (K):

3000 °K 3000 °K

Catalog reference: Catalog reference:


60.6305 60.6306 **Lamp type: Lamp type:**QT-12 QT-12



Pure 2 Downlight designed by Knud Holscher

12V halogen lamp recessed downlight. Remote transformer not included

09.1714.30	White
09.1714.02	Grey
09.1714.14	Black



CERTIFICATIONS

















