

PURE 3 DOWNLIGHT

Number of heads

Mounting Ceiling recessed

Lamps description HIT-CRI G12 Max 150W

Voltage (V) 220/240
Environment Indoor

Notes To be completed with installation frame. Available as

accessory element. Must be ordered separately.

OPTICAL

Light controller descriptionProtection glassAimingAdjustableLight distribution symmetrySymmetricBeam angle44° Wide Flood

ELECTRICAL

Control gear availability

Control gear mounting

Emergency

Insulation class

Separate item
Remote
Without
Class I

PHYSICAL

Cutout diameter (mm) 188

Spot diameter (mm) 135

Construction material Aluminium

Weight (kg) 1,88






Pure 3 Downlight designed by Knud Holscher

Metal halide lamp recessed downlight. Remote control gear not included

09.1802.30 White
09.1802.02 Grey
09.1802.14 Black



CERTIFICATIONS




















Flos.architectural@flos.com www.flos.com



Pure 3 Downlight . Accessories

Optical







Pure 3 Downlight designed by Knud Holscher

08.8168.14

Holding ring

Holding ring

08.8165.68


Elliptical light distribution lens

Elliptical light distribution lens in 4mm thick tempered glass.

08.8171.14

Honeycomb

"honeycomb" anti-glare screen: in thin, blackpainted aluminium sheets.




Metal halide lamp recessed downlight. Remote control gear not included









08.8162.64.OD

Blue filter

Blue filter

08.8162.65.OD

Sky blue filter

Sky blue filter

08.8162.66.OD

Amber filter

Amber filter















GWT 850°

ΙP

20

360°

<u>|</u>

08.8162.67.OD

Red filter

Red filter

08.8162.98.OD


U.V. filter

U.V. filter

08.8162.68

I.R. filter

I.R. filter



Flos.architectural@flos.com www.flos.com

Pure 3 Downlight . Accessories









08.8162.CL

Cold light filter

Cold light filter

08.8162.DL

Daylight filter

Daylight filter

08.8162.ND


Neodimium

Neodimium

Pure 3 Downlight designed by Knud Holscher

Metal halide lamp recessed downlight. Remote control gear not included

09.1802.30 09.1802.02 09.1802.14







08.8162.69


Hot Light

Hot Light

08.8177.68

Flood lens

Flood lens made in press glass.



Mounting







08.8154.00

Installation Frame for No Trim

Installation frame for Pure 3 Downlight No Trim.

HOW TO ORDER

08.8151.30 08.8151.02 08.8151.14

Installation Frame For Trim

Installation frame for Pure 3

CERTIFICATIONS




















FLOS

Pure 3 Downlight . Lamps



60.6481

HIT-CRI

Lamp Watt:

35 W

Lamp category:

Metal halide

Socket:

GI2

Color temperature (K):

3000 °K

Catalog reference:

60.6481

Lamp type:

HIT-CRI



60.6482

HIT-CRI

Lamp Watt:

70 W

Lamp category:

Metal halide

Socket:

GI2

Color temperature (K):

3000 °K

Catalog reference:

60.6482

Lamp type:

HIT-CRI



60.6140

HIT-CRI

Lamp Watt:

70 W

Lamp category:

Metal halide

Socket:

GI2

Color temperature (K):

4200 °K

Catalog reference:

60.6140

Lamp type:


HIT-CRI



Pure 3 Downlight designed by Knud Holscher

Metal halide lamp recessed downlight. Remote control gear not included

09.1802.30 White 09.1802.02 Grey 09.1802.14 Black





60.6141

HIT-CRI

Lamp Watt:

150 W

Lamp category:

Metal halide

Socket: GI2

Color temperature (K):


4200 °K

Catalog reference:

60.6141

Lamp type:

HIT-CRI



CERTIFICATIONS

















