

#### **PURE 3 DOWNLIGHT**

Number of heads

**Mounting** Ceiling recessed

Lamps description HIT-CRI G12 Max 150W

Voltage (V) 220/240
Environment Indoor

Notes To be completed with installation frame. Available as

accessory element. Must be ordered separately.

#### **OPTICAL**

Light controller descriptionProtection glassAimingAdjustableLight distribution symmetrySymmetricBeam angle13° Spot

#### **ELECTRICAL**

Control gear availability

Control gear mounting

Emergency

Insulation class

Separate item
Remote
Without
Class I

#### **PHYSICAL**

Cutout diameter (mm) 188

Spot diameter (mm) 135

Construction material Aluminium

Weight (kg) 1,88






Pure 3 Downlight designed by Knud Holscher

Metal halide lamp recessed downlight. Remote control gear not included

09.1803.30 White
09.1803.02 Grey
09.1803.14 Black



#### **CERTIFICATIONS**




















Flos.architectural@flos.com www.flos.com



## Pure 3 Downlight . Accessories

#### **Optical**









Pure 3 Downlight designed by Knud Holscher

08.8168.14

Holding ring

Holding ring

08.8165.68

Elliptical light distribution lens

Elliptical light distribution lens in 4mm thick tempered glass.

08.8171.14


## Honeycomb

"honeycomb" anti-glare screen: in thin, blackpainted aluminium sheets.




Metal halide lamp recessed downlight. Remote control gear not included









08.8162.64.OD

Blue filter

Blue filter

#### 08.8162.65.OD

Sky blue filter

Sky blue filter

#### 08.8162.66.OD

Amber filter

Amber filter

























08.8162.67.OD

**Red filter** 

Red filter

08.8162.98.OD


U.V. filter

U.V. filter

08.8162.68

I.R. filter

I.R. filter



Flos.architectural@flos.com www.flos.com



Pure 3 Downlight . Accessories









08.8162.CL

Cold light filter

Cold light filter

08.8162.DL

#### Daylight filter

Daylight filter

08.8162.ND

#### Neodimium

Neodimium

Pure 3 Downlight designed by Knud Holscher

Metal halide lamp recessed downlight. Remote control gear not included





08.8162.69


# **Hot Light**

Hot Light

08.8177.68


# Flood lens

Flood lens made in press glass.



## Mounting







#### **CERTIFICATIONS**

















08.8154.00

# Installation Frame for No Trim

Installation frame for Pure 3 Downlight No Trim.

**HOW TO ORDER** 

08.8151.30



08.8151.02



08.8151.14

#### **Installation Frame For Trim**

Installation frame for Pure 3 Downlight Trim.

Flos.architectural@flos.com www.flos.com

# **FLOS**

#### Pure 3 Downlight . Lamps



60.6481

HIT-CRI

Lamp Watt:

35 W

Lamp category:

Metal halide

Socket:

GI2

Color temperature (K):

3000 °K

Catalog reference:

60.6481

Lamp type:

HIT-CRI



60.6482

HIT-CRI

Lamp Watt:

70 W

Lamp category:

Metal halide

Socket:

GI2

Color temperature (K):

3000 °K

Catalog reference:

60.6482

Lamp type:

HIT-CRI



60.6140

HIT-CRI

Lamp Watt:

70 W

Lamp category:

Metal halide

Socket:

GI2

Color temperature (K):

4200 °K

Catalog reference:

60.6140

Lamp type:


HIT-CRI



Pure 3 Downlight designed by Knud Holscher

Metal halide lamp recessed downlight. Remote control gear not included

09.1803.30 White
09.1803.02 Grey
09.1803.14 Black





60.6141

HIT-CRI

Lamp Watt:

150 W

Lamp category:

Metal halide

Socket: GI2

Color temperature (K):

4200 °K

Catalog reference:

60.6141

Lamp type:

HIT-CRI

# CERTIFICATIONS

















