

FLOS

PURE I SPOT TRACK

Number of heads	1
Mounting	Track mounting
Lamps description	Power LED 15,7W 1400 lm 2700K CRI 80
Luminaire luminous flux	Extreme Cut-off. See reference number
Voltage (V)	220/240
Environment	Indoor

OPTICAL

Reflector finish	Aluminum
Aiming	Adjustable
Light distribution symmetry	Symmetric
Beam angle	15° Spot

ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic
Emergency	Without
Insulation class	Class I

PHYSICAL



Width (mm)	180
Spot diameter (mm)	86
Construction material	Aluminium
Weight (kg)	1,20




Pure I Spot Track
designed by Knud Holscher

Projector for mounting on threephase rail with LED light source. 220-240V, 50-60Hz power supply included.

● 09.2405.30A - 1148lm	White
● 09.2405.02A - 1148lm	Grey
● 09.2405.14A - 1148lm	Black



CERTIFICATIONS



Pure I Spot Track . Accessories

Optical



08.8166.14

Holding ring



08.8163.68

Elliptical lens

Elliptical light distribution lens in 4 mm thick tempered glass.



08.8169.14

Honeycomb


"Honeycomb" anti-glare screen: in thin, blackpainted aluminium sheets.



Pure I Spot Track
designed by Knud Holscher

Projector for mounting on threephase rail with LED light source. 220-240V, 50-60Hz power supply included.


- 09.2405.30A - 1148lm White
- 09.2405.02A - 1148lm Grey
- 09.2405.14A - 1148lm Black



08.8160.64.OD

Blue filter


Blue filter



08.8160.65.OD

Sky blue filter



Sky blue filter



08.8160.66.OD

Amber filter

Amber filter



08.8160.67.OD

Red filter

Red filter



08.8160.98.OD

U.V. filter

U.V. filter



08.8160.68

I.R. filter

I.R. filter

CERTIFICATIONS




Pure I Spot Track . Accessories



08.8160.69

Hot Light


Hot Light



08.8160.CL

Cold light filter

Cold light filter



08.8160.DL

Daylight filter

Daylight filter



Pure I Spot Track

designed by Knud Holscher

Projector for mounting on threephase rail with LED light source. 220-240V, 50-60Hz power supply included.

- 09.2405.30A - 1148lm White
- 09.2405.02A - 1148lm Grey
- 09.2405.14A - 1148lm Black



08.8160.ND

Neodimium



08.8175.68

Flood lens

Flood lens made in press glass.




08.8232.30

08.8232.02

08.8232.14

Pure I Pro external ring accessory

Pure I Pro external ring accessory. Only for halogen and halide lamps, consult for LED version



CERTIFICATIONS



Pure I Spot Track . Lamps



Power LED

Lamp category:
LED

Socket:
Special base


Lamp type:
Power LED



Pure I Spot Track
designed by Knud Holscher

Projector for mounting on threephase rail with LED light source. 220-240V, 50-60Hz power supply included.

- 09.2405.30A - 1148lm White
- 09.2405.02A - 1148lm Grey
- 09.2405.14A - 1148lm Black



CERTIFICATIONS

