FLOS

PURE I SPOT PRO TRACK

Number of heads

Mounting Track mounting

Lamps descriptionPower LED 15,7W 1400 lm 3000K CRI 80Luminaire luminous fluxExtreme Cut-off. See reference number

Voltage (V) 220/240 Environment Indoor

OPTICAL

Reflector finish Aluminum
Aiming Adjustable
Light distribution symmetry Symmetric
Beam angle 14° Spot

ELECTRICAL

Transformer availability Included
Transformer mounting Integral
Transformer type Electronic
Emergency Without
Insulation class Class I

PHYSICAL

Width (mm) 180 Spot diameter (mm) 86

Construction material Aluminium
Weight (kg) 1,40






Pure I Spot Pro Track designed by Knud Holscher

Projector for mounting on threephase rail with LED light source. 220-240V, 50-60Hz power supply included.

09.2435.30A - 966lm White
09.2435.02A - 966lm Grey
09.2435.14A - 966lm Black



CERTIFICATIONS










20









Flos.architectural@flos.com www.flos.com



Pure I Spot Pro Track . Accessories

Optical









Pure I Spot Pro Track designed by Knud Holscher

08.8163.68 **Elliptical lens**

Elliptical light distribution lens in 4 mm thick tempered glass. 08.8160.64.OD

Blue filter

Blue filter

08.8160.65.OD

Sky blue filter

Sky blue filter

Projector for mounting on threephase rail with LED light source. 220-240V, 50-60Hz power supply included.







09.2435.30A - 966lm White 09.2435.02A - 966lm Grey 09.2435.14A - 966lm Black

08.8160.66.OD

Amber filter

Amber filter

08.8160.67.OD

Red filter


Red filter



08.8160.98.OD

U.V. filter

U.V. filter



















ΙP 20

08.8160.69

Hot Light


Hot Light



08.8160.CL

Cold light filter

Cold light filter



08.8160.68

I.R. filter

I.R. filter

Flos.architectural@flos.com www.flos.com

FLOS

Pure I Spot Pro Track . Accessories







08.8160.DL

08.8160.ND

08.8175.68

Daylight filter

Daylight filter

Neodimium

Flood lens

Flood lens made in press glass.



Pure I Spot Pro Track designed by Knud Holscher

Projector for mounting on threephase rail with LED light source. 220-240V, 50-60Hz power supply included.


09.2435.30A - 966lm White 09.2435.02A - 966lm Grey 09.2435.14A - 966lm Black



08.8186.14

Honeycomb

Anti-glare grid in aluminium cells with black liquid paint finish.



CERTIFICATIONS




















Flos.architectural@flos.com www.flos.com



Pure I Spot Pro Track . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:


Power LED



Pure I Spot Pro Track designed by Knud Holscher

Projector for mounting on threephase rail with LED light source. 220-240V, 50-60Hz power supply included.

09.2435.30A - 966lm White 09.2435.02A - 966lm Grey 09.2435.14A - 966lm Black



CERTIFICATIONS

















www.flos.com

