

PURE I SPOT PRO CEILING

Number of heads

Mounting Ceiling surface

Lamps descriptionPower LED 15,7W 1400 lm 3000K CRI 80Luminaire luminous fluxExtreme Cut-off. See reference number

Voltage (V) 220/240 Environment Indoor

OPTICAL

Reflector finishAluminumAimingAdjustableLight distribution symmetrySymmetricBeam angle30° Flood

ELECTRICAL

Transformer availability Included
Transformer mounting Integral
Transformer type Electronic
Emergency Without
Insulation class Class I

PHYSICAL

Width (mm) 180 Spot diameter (mm) 86

Construction material Aluminium
Weight (kg) 1,40






Pure I Spot Pro Ceiling designed by Knud Holscher

Projector for mounting in ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

09.2487.30A - 719lm	White
09.2487.02A - 719lm	Grey
99.2487.14A - 719lm	Black



CERTIFICATIONS

















Flos.architectural@flos.com www.flos.com



Pure I Spot Pro Ceiling . Accessories

Optical









08.8163.68

Elliptical lens

Elliptical light distribution lens in 4 mm thick tempered glass.

08.8160.64.OD

Blue filter

Blue filter

08.8160.65.OD

Sky blue filter

Sky blue filter

Pure I Spot Pro Ceiling designed by Knud Holscher


Projector for mounting in ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

09.2487.30A - 719lm	White
09.2487.02A - 719lm	Grey
99.2487.14A - 719lm	Black









08.8160.66.OD

Amber filter

Amber filter

08.8160.67.OD

Red filter

Red filter

08.8160.69

Hot Light

Hot Light

08.8160.98.OD

U.V. filter

U.V. filter











₹

900 900







08.8160.68

I.R. filter

I.R. filter



08.8160.CL

Cold light filter

Cold light filter



Flos.architectural@flos.com www.flos.com



Pure I Spot Pro Ceiling . Accessories







08.8160.DL

Daylight filter

Daylight filter

08.8160.ND

Neodimium

08.8175.68

Flood lens

Flood lens made in press glass.



Pure I Spot Pro Ceiling designed by Knud Holscher

Projector for mounting in ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.


09.2487.30A - 719lm White 09.2487.02A - 719lm Grey 09.2487.14A - 719lm Black



08.8186.14

Honeycomb

Anti-glare grid in aluminium cells with black liquid paint finish.



CERTIFICATIONS















IP 20

Flos.architectural@flos.com www.flos.com



Pure I Spot Pro Ceiling . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:


Power LED



Pure I Spot Pro Ceiling designed by Knud Holscher

Projector for mounting in ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

09.2487.30A - 719lm	White
09.2487.02A - 719lm	Grey
09.2487.14A - 719lm	Black



CERTIFICATIONS















IP 20