

#### **SOLID PURE TRACK DALI VERSION**

Number of heads

**Design awards** Red Dot Design Award Winner 2013

Mounting Three phase track

Lamps description LED Array 23W 2231 lm 3000K CRI 90

Luminaire luminous flux See reference number

Voltage (V) 220/240 Environment Indoor

#### **OPTICAL**

Light controller descriptionProtection glassAimingAdjustableLight distribution symmetrySymmetricBeam angle17° Medium

### **ELECTRICAL**


Transformer availability Included
Transformer mounting Integral

Transformer type Electronic dimmable dali

Emergency Without Insulation class Class I

# **PHYSICAL**

Diameter (mm)S/NHeight (mm)239,5Spot diameter (mm)103Construction materialAluminiumWeight (kg)1,70






**Solid Pure Track Dali Version** designed by Knud Holscher

Spotlight to be installed on 3-circuittrack with LED light source. Integrated power supply 220-240V / 50-60Hz.

09.2886.30.DA - 1810lm White
09.2886.14.DA - 1810lm Black



#### **CERTIFICATIONS**

















Flos.architectural@flos.com www.flos.com



#### Solid Pure Track Dali Version . Accessories

# **Optical**









08.8768.14

**Holding ring** 

Holding ring

08.8763.14

Honeycomb anti-glare screen

"Honeycomb" anti-glare screen: in thin, black-painted aluminium sheets.

08.8766.64.OD

**Blue filter** 

Blue filter

Solid Pure Track Dali Version designed by Knud Holscher

Spotlight to be installed on 3-circuittrack with LED light source. Integrated power supply 220-240V / 50-60Hz.

09.2886.30.DA - 1810lm White
09.2886.14.DA - 1810lm Black









Sky blue filter

Sky blue filter






08.8766.67.OD

**Amber filter** 

Amber filter

Red filter

Red filter



## **CERTIFICATIONS**

















Flos.architectural@flos.com www.flos.com



# Solid Pure Track Dali Version . Lamps



**LED Array** 

Lamp category:

LED

Socket:

Special base

Lamp type:


LED Array



**Solid Pure Track Dali Version** designed by Knud Holscher

Spotlight to be installed on 3-circuittrack with LED light source. Integrated power supply 220-240V / 50-60Hz.

09.2886.30.DA - 1810lm White 09.2886.14.DA - 1810lm Black



## **CERTIFICATIONS**













