# FLOS

## SOLID PURE TRACK DALI VERSION

Number of heads	I.
Design awards	Red
Mounting	Thre
Lamps description	LED
Luminaire luminous flux	See
Voltage (V)	220/
Environment	Indo

Red Dot Design Award Winner 2013 Three phase track LED Array 23W 2865 Im 4000K CRI 80 See reference number 220/240 Indoor

## OPTICAL

Light controller description Aiming Light distribution symmetry Beam angle

## ELECTRICAL

Transformer availability Transformer mounting Transformer type Emergency Insulation class

## PHYSICAL

Diameter (mm)
Height (mm)
Spot diameter (mm)
Construction material
Weight (kg)

Flos.architectural@flos.com

Included Integral Electronic dimmable dali Without Class I

Protection glass

Adjustable

Symmetric

10° Spot

S/N


239,5 103 Aluminium


# 




Solid Pure Track Dali Version designed by Knud Holscher

Spotlight to be installed on 3-circuittrack with LED light source. Integrated power supply 220-240V / 50-60Hz.





## CERTIFICATIONS



# FLOS

## Solid Pure Track Dali Version . Accessories



# CERTIFICATIONS

## FLOS

Solid Pure Track Dali Version . Lamps



LED Array LED Socket: Special base Lamp type: LED Array



Solid Pure Track Dali Version designed by Knud Holscher

Spotlight to be installed on 3-circuittrack with LED light source. Integrated power supply 220-240V / 50-60Hz.



