

#### **SOLID PURE TRACK NO DIMMABLE**

Number of heads

**Design awards** Red Dot Design Award Winner 2013

**Mounting** Three phase track

Lamps description LED Array 35W 4321 lm 3000K CRI 80

Luminaire luminous flux See reference number

Voltage (V) 220/240 Environment Indoor

#### **OPTICAL**

Light controller descriptionProtection glassAimingAdjustableLight distribution symmetrySymmetricBeam angle15° Spot

#### **ELECTRICAL**

Transformer availability Included
Transformer mounting Integral
Transformer type Electronic
Emergency Without
Insulation class Class I

# **PHYSICAL**

Diameter (mm)S/NHeight (mm)239,5Spot diameter (mm)103Construction materialAluminiumWeight (kg)1,70






# **Solid Pure Track No Dimmable** designed by Knud Holscher

Spotlight to be installed on 3-circuittrack with LED light source. Integrated power supply 220-240V / 50-60Hz.

09.2953.30 - 3473lm White 09.2953.14 - 3473lm Black



#### **CERTIFICATIONS**

















rchitectural@flos.com www.flos.com



#### Solid Pure Track No Dimmable . Accessories

### **Optical**







Teo \_\_\_

08.8768.14

**Holding ring** 

Holding ring

08.8763.14

Honeycomb anti-glare screen

"Honeycomb" anti-glare screen: in thin, black-painted aluminium sheets.

08.8766.64.OD

**Blue filter** 

Blue filter

**Solid Pure Track No Dimmable** designed by Knud Holscher

Spotlight to be installed on 3-circuittrack with LED light source. Integrated power supply 220-240V / 50-60Hz.

09.2953.30 - 3473lm White 09.2953.14 - 3473lm Black









Sky blue filter

Sky blue filter

08.8766.66.OD


Amber filter

Amber filter

08.8766.67.OD

**Red filter** 

Red filter



# **CERTIFICATIONS**



















### Solid Pure Track No Dimmable . Accessories

### Mounting





60.3022.11

60.3023.11 60.3023.14 60.3023.29

Recessed box for fixpoint



# Solid Pure Track No Dimmable . Lamps



**LED Array** 

Lamp category:

LED

Socket:

Special base

Lamp type:


LED Array



# **Solid Pure Track No Dimmable** designed by Knud Holscher

Spotlight to be installed on 3-circuittrack with LED light source. Integrated power supply 220-240V / 50-60Hz.

09.2953.30 - 3473lm White 09.2953.14 - 3473lm Black



# **CERTIFICATIONS**

















Flos.architectural@flos.com www.flos.com