

SOLID PURE TRACK NO DIMMABLE

Number of heads

Red Dot Design Award Winner 2013 Design awards

Mounting Three phase track

Lamps description LED Array 35W 4508 lm 4000K CRI 80

Luminaire luminous flux See reference number

220/240 Voltage (V) **Environment** Indoor

OPTICAL

Light controller description Protection glass **Aiming** Adjustable Light distribution symmetry Symmetric Beam angle 23° Medium

ELECTRICAL

Transformer availability Included Transformer mounting Integral Transformer type Electronic Without **Emergency** Class I **Insulation class**

PHYSICAL

Diameter (mm) S/N Height (mm) 239,5 103 Spot diameter (mm) **Construction material** Aluminium 1,70 Weight (kg)






Solid Pure Track No Dimmable designed by Knud Holscher

Spotlight to be installed on 3-circuittrack with LED light source. Integrated power supply 220-240V / 50-60Hz.

09.2960.30 - 3614lm White 09.2960.14 - 3614lm Black



CERTIFICATIONS

















www.flos.com



Solid Pure Track No Dimmable . Accessories

Optical









08.8768.14

Holding ring

Holding ring

08.8763.14

Honeycomb anti-glare screen

"Honeycomb" anti-glare screen: in thin, black-painted aluminium sheets.

08.8766.64.OD

Blue filter

Blue filter

Solid Pure Track No Dimmable designed by Knud Holscher

Spotlight to be installed on 3-circuittrack with LED light source. Integrated power supply 220-240V / 50-60Hz.

09.2960.30 - 3614lm White
09.2960.14 - 3614lm Black









08.8766.65.OD

Sky blue filter

Sky blue filter

08.8766.66.OD


Amber filter

Amber filter

08.8766.67.OD

Red filter

Red filter



CERTIFICATIONS

















Flos.architectural@flos.com www.flos.com



Solid Pure Track No Dimmable . Accessories

Mounting





60.3022.11

60.3023.11 60.3023.14 60.3023.29

Fix-point

Recessed box for fixpoint

Solid Pure Track No Dimmable . Lamps



LED Array

Lamp category:

LED

Socket:

Special base

Lamp type:


LED Array



Solid Pure Track No Dimmable designed by Knud Holscher

Spotlight to be installed on 3-circuittrack with LED light source. Integrated power supply 220-240V / 50-60Hz.

09.2960.30 - 3614lm White 09.2960.14 - 3614lm Black



CERTIFICATIONS

















Flos.architectural@flos.com www.flos.com