# FLOS

## SOLID PURE TRACK DALI VERSION

Number of heads	I
Design awards	Ree
Mounting	Th
Lamps description	LED
Luminaire luminous flux	See
Voltage (V)	220
Environment	Ind

Red Dot Design Award Winner 2013 Three phase track LED Array 53W 4312 Im 3000K CRI 90 See reference number 220/240 Indoor

## OPTICAL

Light controller description Aiming Light distribution symmetry Beam angle

## ELECTRICAL

Transformer availability Transformer mounting Transformer type Emergency Insulation class

## PHYSICAL

Diameter (mm)
Height (mm)
Spot diameter (mm)
Construction material
Weight (kg)

Flos.architectural@flos.com

Included Integral Electronic dimmable dali Without Class I

Protection glass

Adjustable

Symmetric

45° Flood

S/N

239,5 103 Aluminium


# 




Solid Pure Track Dali Version designed by Knud Holscher

Spotlight to be installed on 3-circuittrack with LED light source. Integrated power supply 220-240V / 50-60Hz.





## CERTIFICATIONS



# FLOS

## Solid Pure Track Dali Version . Accessories



# CERTIFICATIONS

## FLOS

Solid Pure Track Dali Version . Lamps



LED Array LED Socket: Special base Lamp type: LED Array



Solid Pure Track Dali Version designed by Knud Holscher

Spotlight to be installed on 3-circuittrack with LED light source. Integrated power supply 220-240V / 50-60Hz.



