## FLOS

### SOLID PURE TRACK DALI VERSION

Number of heads	I
Design awards	Red Dot Desig
Mounting	Three phase to
Lamps description	LED Array 30
Luminaire luminous flux	See reference
Voltage (V)	220/240
Environment	Indoor

Red Dot Design Award Winner 2013 Three phase track LED Array 30W 2855 Im 3000K CRI 90 See reference number 220/240 Indoor

### OPTICAL

Light controller description Aiming Light distribution symmetry Beam angle

### ELECTRICAL

Transformer availability Transformer mounting Transformer type Emergency Insulation class

### PHYSICAL

Diameter (mm) Height (mm) Spot diameter (mm) Construction material Weight (kg)

Flos.architectural@flos.com

S/N 239,5

Electronic dimmable dali

Protection glass

Adjustable

Symmetric

14° Spot

Included

Integral

Without

Class I

103


Aluminium 1,70







Solid Pure Track Dali Version designed by Knud Holscher

Spotlight to be installed on 3-circuittrack with LED light source. Integrated power supply 220-240V / 50-60Hz.





### CERTIFICATIONS



## FLOS

### Solid Pure Track Dali Version . Accessories



# CERTIFICATIONS

### FLOS

Solid Pure Track Dali Version . Lamps



LED Array LED Socket: Special base Lamp type: LED Array



Solid Pure Track Dali Version designed by Knud Holscher

Spotlight to be installed on 3-circuittrack with LED light source. Integrated power supply 220-240V / 50-60Hz.



