## FLOS

### SOLID PURE TRACK DALI VERSION

Number of heads	I
Design awards	Rec
Mounting	Thr
Lamps description	LEC
Luminaire luminous flux	See
Voltage (V)	220
Environment	Inde

d Dot Design Award Winner 2013 ree phase track D Array 30W 2855 lm 3000K CRI 90 e reference number 0/240 loor

### **OPTICAL**

Light controller description Aiming Light distribution symmetry **Beam angle** 

### ELECTRICAL

Transformer availability **Transformer mounting** Transformer type Emergency Insulation class

### PHYSICAL

D H Sp C N

Flos.architectural@flos.com

Integral Electronic dimmable dali Without Class I

Protection glass

Adjustable

Symmetric

44° Flood

Included

S/N

103

1,70

239,5

Aluminium


liameter (mm)
leight (mm)
pot diameter (mm)
onstruction material
Veight (kg)







Solid Pure Track Dali Version designed by Knud Holscher

Spotlight to be installed on 3-circuit-track with LED light source. Integrated power supply 220-240V / 50-60Hz.





### CERTIFICATIONS



## FLOS

### Solid Pure Track Dali Version . Accessories



# CERTIFICATIONS

### FLOS

Solid Pure Track Dali Version . Lamps



LED Array LED Socket: Special base Lamp type: LED Array



Solid Pure Track Dali Version designed by Knud Holscher

Spotlight to be installed on 3-circuittrack with LED light source. Integrated power supply 220-240V / 50-60Hz.



