

UT SPOT TRACK Ø57 ON BOARD DIMMER INCLUDED

Number of heads

Mounting Track mounting

Lamps description LED Array 21,5W 2150 lm 4000K CRI 90

Luminaire luminous flux See reference number

Voltage (V) 220/240 **Environment** Indoor

Notes

Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with Honeycomb + Lense at the same time. FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium.

Compatibility with Eutrac under request.



Reflector finish Aluminum **Aiming** Adjustable Light distribution symmetry Symmetric 39° Flood Beam angle

ELECTRICAL

Transformer availability Included Transformer mounting Integral

Transformer type Electronic dimmable

Emergency Without **Insulation class** Class II

PHYSICAL

Spot diameter (mm) 57

Aluminium **Construction material** Weight (kg) 0,57






UT Spot Track Ø57 On Board **Dimmer Included**

designed by FLOS Architectural

Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

09.4452.30A - 1847lm White 09.4452.14A - 1847lm Black



CERTIFICATIONS





















UT Spot Track Ø57 On Board Dimmer Included . Accessories

Optical











08.8431.00 **Elliptical Lens** 08.8432.00

Flood Lens

designed by FLOS Architectural

Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.



Screening Crosspiece



09.4452.30A - 1847lm 09.4452.14A - 1847lm

White Black


08.8428.00

Honeycomb



08.0526.00

Snoot Shielding Cone



CERTIFICATIONS

















ΙP 20

Flos.architectural@flos.com www.flos.com



UT Spot Track Ø57 On Board Dimmer Included . Lamps



LED Array

Lamp category:

LED

Socket:

Special base

Lamp type:

LED Array




UT Spot Track Ø57 On Board Dimmer Included

designed by FLOS Architectural

Spotlight to be installed on 3-phase track. with LED light source. 220-240V, 50-60Hz power supply integrated.

09.4452.30A - 1847lm White
09.4452.14A - 1847lm Black



CERTIFICATIONS

















1P 20

Flos.architectural@flos.com www.flos.com