

UT SPOT CEILING Ø86

Number of heads	1
Mounting	Ceiling surface
Lamps description	LED Array High Performances 32,8W 3770 lm 3000K CRI 80
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor



OPTICAL

Reflector finish	Aluminum
Aiming	Adjustable
Light distribution symmetry	Symmetric
Beam angle	24° Medium

UT Spot Ceiling Ø86

designed by FLOS Architectural

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.


ELECTRICAL

Transformer availability	Included
Transformer mounting	Remote
Transformer type	Electronic
Emergency	Without
Insulation class	Class II


● 09.4861.30A - 2528lm	White
● 09.4861.14A - 2528lm	Black

PHYSICAL

Cutout diameter (mm)	90
Spot diameter (mm)	86
Construction material	Aluminium
Weight (kg)	1,66



CERTIFICATIONS



UT Spot Ceiling Ø86 . Accessories

Optical



○ 08.8163.68

Elliptical lens

Elliptical light distribution lens in 4 mm thick tempered glass.



○ 08.8175.68

Flood lens

Flood lens made in press glass.



● 08.8495.14

Honeycomb

"Honeycomb" anti-glare screen: in thin, black-painted aluminium sheets.



● 08.8410.00

Holding ring

Holding ring



● 08.8411.00

Screening crosspiece




UT Spot Ceiling Ø86 designed by FLOS Architectural

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.

○ 09.4861.30A - 2528lm White

● 09.4861.14A - 2528lm Black



CERTIFICATIONS



UT Spot Ceiling Ø86 . Lamps



LED Array

Lamp category:

LED

Socket:

Special base

Lamp type:

LED Array




UT Spot Ceiling Ø86

designed by FLOS Architectural

Spotlight to be installed on ceiling with LED light source. 220-240V, 50-60Hz remote power supply included.

- 09.4861.30A - 2528lm White
- 09.4861.14A - 2528lm Black



CERTIFICATIONS

