

#### UT DOWNLIGHT NO TRIM Ø86 NON DIMMABLE

Number of heads

**Mounting** Ceiling recessed

**Lamps description** LED Array High Performances 27W 3214 lm 3000K CRI 80

Luminaire luminous flux See reference number

Voltage (V) 220/240 Environment Indoor

**Notes** Pre-installation frame must be ordered separately.

#### **OPTICAL**

Reflector finishAluminumAimingAdjustableLight distribution symmetrySymmetricBeam angle24° Medium

#### **ELECTRICAL**

Transformer availability Included
Transformer mounting Remote
Transformer type Electronic
Emergency Without
Insulation class Class II

### **PHYSICAL**

Cutout diameter (mm) 132 Spot diameter (mm) 86

Construction material Aluminium Weight (kg) 0,97








UT Downlight No Trim Ø86 Non Dimmable designed by FLOS Architectural

Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.<nextline>

09.4920.30A - 2154lm White
09.4920.14A - 2154lm Black



#### **CERTIFICATIONS**

















Flos.architectural@flos.com www.flos.com



## UT Downlight No Trim Ø86 Non Dimmable . Accessories

#### Mounting



08.8995.30

08.8995.14

**Installation frame NO TRIM** 



UT Downlight No Trim Ø86 Non Dimmable designed by FLOS Architectural

Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.<nextline>


09.4920.30A - 2154lm White 09.4920.14A - 2154lm Black

#### **Optical**









08.8163.68

**Elliptical lens** 

Elliptical light distribution lens in 4 mm thick tempered glass. 08.8175.68

Flood lens

Flood lens made in press glass.

08.8495.14

Honeycomb

"Honeycomb" anti-glare screen: in thin, black-painted aluminium

**CERTIFICATIONS** 



900













Flos.architectural@flos.com www.flos.com



## UT Downlight No Trim Ø86 Non Dimmable . Accessories







08.8411.00

Holding ring

Screening crosspiece

Holding ring



designed by FLOS Architectural

Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.<nextline>

09.4920.30A - 2154lm

## White 09.4920.14A - 2154lm Black

# UT Downlight No Trim Ø86 Non Dimmable . Lamps



**LED Array** 

Lamp category:


LED

Socket:

Special base

Lamp type:

LED Array



## **CERTIFICATIONS**

















Flos.architectural@flos.com www.flos.com