

#### UT DOWNLIGHT NO TRIM Ø86 NON DIMMABLE

Number of heads

**Mounting** Ceiling recessed

**Lamps description** LED Array High Performances 27W 2767 lm 4000K CRI 90

Luminaire luminous flux See reference number

Voltage (V) 220/240 Environment Indoor

**Notes** Pre-installation frame must be ordered separately.

#### **OPTICAL**

Reflector finishAluminumAimingAdjustableLight distribution symmetrySymmetricBeam angle24° Medium

## **ELECTRICAL**

Transformer availability Included
Transformer mounting Remote
Transformer type Electronic
Emergency Without
Insulation class Class II

## **PHYSICAL**

Cutout diameter (mm) 132 Spot diameter (mm) 86

Construction material Aluminium Weight (kg) 0,97






UT Downlight No Trim Ø86 Non Dimmable designed by FLOS Architectural

Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.<nextline>

09.4926.30A - 1855Im White
09.4926.14A - 1855Im Black



#### **CERTIFICATIONS**

















Flos.architectural@flos.com www.flos.com



## UT Downlight No Trim Ø86 Non Dimmable . Accessories

#### Mounting



08.8995.30

08.8995.14

Installation frame NO TRIM



UT Downlight No Trim Ø86 Non Dimmable designed by FLOS Architectural

Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.<nextline>


09.4926.30A - 1855lm White 09.4926.14A - 1855lm Black

### **Optical**









08.8163.68

Elliptical lens

Elliptical light distribution lens in 4 mm thick tempered glass.

08.8175.68

Flood lens

Flood lens made in press glass.

08.8495.14

Honeycomb

"Honeycomb" anti-glare screen: in thin, black-painted aluminium

CERTIFICATIONS















Flos.architectural@flos.com www.flos.com



# UT Downlight No Trim Ø86 Non Dimmable . Accessories








08.8411.00

Holding ring

Screening crosspiece

Holding ring



White

Black

09.4926.30A - 1855lm

09.4926.14A - 1855lm

# UT Downlight No Trim Ø86 Non Dimmable . Lamps



**LED Array** 

Lamp category:

LED

Socket:

Special base


Lamp type:


LED Array



UT Downlight No Trim Ø86 Non Dimmable designed by FLOS Architectural

Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.<nextline>





# CERTIFICATIONS

















Flos.architectural@flos.com www.flos.com