

UT SPOT TRACK MULTICHIP Ø86

Number of heads	1
Mounting	Track mounting
Lamps description	Top LED 11,5W 900 lm 3000K CRI 80
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	FLOS three-phase lighting track luminaires are designed and fully tested for tracks recommended by FLOS. Compatibility is guaranteed with three-phase track produced by Nordic Aluminium. Compatibility with Eutrac under request.



UT Spot Track Multichip Ø86 designed by FLOS Architectural

Spotlight to be installed on 3-phase track, with LED light source. 220-240V, 50-60Hz power supply integrated.

● 09.4983.30 - 776lm	White
● 09.4983.14 - 776lm	Black

OPTICAL


Reflector finish	Aluminum
Aiming	Adjustable
Light distribution symmetry	Symmetric
Beam angle	8° Super Spot

ELECTRICAL


Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic
Emergency	Without
Insulation class	Class II

PHYSICAL

Spot diameter (mm)	86
Construction material	Aluminium
Weight (kg)	1,18



CERTIFICATIONS



UT Spot Track Multichip Ø86 . Lamps



Top LED

Lamp category:
LED

Socket:
Special base


Lamp type:
Top LED



UT Spot Track Multichip Ø86 designed by FLOS Architectural

Spotlight to be installed on 3-phase track, with LED light source.
220-240V, 50-60Hz power supply integrated.

- 09.4983.30 - 776lm White
- 09.4983.14 - 776lm Black



CERTIFICATIONS

