

#### **UT PRO 150 GA-69 ON BOARD DIMMER INCLUDED**

**Number of heads** 

**Mounting** Track mounting GA

LED Array 23,5W 2009 Im 4000K CRI 90 Lamps description

See reference number Luminaire luminous flux

Voltage (V) 120/270 **Environment** Indoor

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing Notes

any fastening accessory. Installation compatible with

honeycomb + lense at the same time.

## **OPTICAL**

Reflector finish Borosilicate glass reflector

**Aiming** Adjustable Light distribution symmetry Symmetric Beam angle 40° Flood

#### **ELECTRICAL**

Transformer availability Included **Transformer mounting** Integral

Transformer type Electronic dimmable

Without **Emergency Insulation class** Class I

#### **PHYSICAL**

Spot diameter (mm) 57

**Construction material** Aluminium Weight (kg) 0,52






#### UT Pro 150 GA-69 On Board **Dimmer Included**

designed by FLOS Architectural

Spotlight to be installed in standard 3phase track with LED light source. 120-270V power supply integrated. nextline>

09.7275.40A - 1915lm White 09.7275.14A - 1915lm Black



## **CERTIFICATIONS**



















www.flos.com



### UT Pro 150 GA-69 On Board Dimmer Included . Accessories

### **Optical**







08.8429.00

08.8431.00

08.8432.00

**Screening Crosspiece** 

**Elliptical Lens** 

Flood Lens





08.8428.00

Honeycomb

08.0526.00

**Snoot Shielding Cone** 




# UT Pro 150 GA-69 On Board Dimmer Included

designed by FLOS Architectural

Spotlight to be installed in standard 3phase track with LED light source. 120-270V power supply integrated. nextline>

09.7275.40A - 1915lm White 09.7275.14A - 1915lm Black



# **CERTIFICATIONS**











20









# UT Pro 150 GA-69 On Board Dimmer Included . Lamps



**LED Array** 

Lamp category:

LED

Socket:

Special base

Lamp type:

LED Array




# UT Pro 150 GA-69 On Board Dimmer Included

designed by FLOS Architectural

Spotlight to be installed in standard 3phase track with LED light source. I 20-270V power supply integrated.< nextline>

09.7275.40A - 1915lm White
09.7275.14A - 1915lm Black



## **CERTIFICATIONS**

















IP 20

Flos.architectural@flos.com www.flos.com