

## UT PRO 175 ON BOARD DIMMER INCLUDED

<b>Number of heads</b>	1
<b>Mounting</b>	Track mounting
<b>Lamps description</b>	LED Array 35,3W 3950 lm 3000K CRI 80
<b>Luminaire luminous flux</b>	See reference number
<b>Voltage (V)</b>	120/270
<b>Environment</b>	Indoor
<b>Notes</b>	Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.



### OPTICAL

<b>Reflector finish</b>	Borosilicate glass reflector
<b>Aiming</b>	Adjustable
<b>Light distribution symmetry</b>	Symmetric
<b>Beam angle</b>	35° Flood

### ELECTRICAL

<b>Transformer availability</b>	Included
<b>Transformer mounting</b>	Integral
<b>Transformer type</b>	Electronic dimmable
<b>Emergency</b>	Without
<b>Insulation class</b>	Class I



### PHYSICAL

<b>Spot diameter (mm)</b>	75
<b>Construction material</b>	Aluminium


### UT Pro 175 On Board Dimmer Included designed by FLOS Architectural

Spotlight to be installed in Tracking Power profile with LED light source. 120-270V power supply integrated.<nextline>

● 09.7306.40 - 3321lm	White
● 09.7306.14 - 3321lm	Black



### CERTIFICATIONS



## UT Pro 175 On Board Dimmer Included . Accessories

### Optical



● 08.9108.00  
**Screening Crosspiece**



○ 08.9109.00  
**Elliptical Lens**



○ 08.9110.00  
**Flood Lens**



● 08.9107.00  
**Honeycomb**




● 08.9111.00  
**Snoot Shielding Cone**



**UT Pro 175 On Board Dimmer Included**  
designed by FLOS Architectural

Spotlight to be installed in Tracking Power profile with LED light source. 120-270V power supply integrated.<nextline>

- 09.7306.40 - 3321lm White
- 09.7306.14 - 3321lm Black



### CERTIFICATIONS



## UT Pro 175 On Board Dimmer Included . Lamps



**LED Array**

**Lamp category:**

LED

**Socket:**

Special base

**Lamp type:**


LED Array



**UT Pro 175 On Board Dimmer Included**  
designed by FLOS Architectural

Spotlight to be installed in Tracking Power profile with LED light source. 120-270V power supply integrated.< nextline>

- 09.7306.40 - 3321lm White
- 09.7306.14 - 3321lm Black



### CERTIFICATIONS

